D70/22.P



Products Low Voltage Products and Systems Connection Devices Terminal Blocks SNA Series

General Information	
Extended Product Type:	D70/22.P
Product ID:	1SNA400772R1300
EAN:	3472594007722
Catalog Description:	D70/22.P Screw Clamp Terminal Blocks - Ground - Green-Yellow
Long Description:	Reliable electrical and mechanical contact with the rail.
Additional Information	
ABB Industrial IT Suite:	Control IT
Ambient Air Temperature:	Operation -55 +110 °C Storage -55 +110 °C
Ambient Temperature:	-5 +40 °C
CSA Certificate:	1SND161051A0202
Color:	Green-Yellow
Connecting Capacity Main Circuit UL/CSA:	Screw Clamp / Flexible 1x 4 00 AWG Screw Clamp / Rigid 1x 4 00 AWG Screw Clamp / With Insulated Ferrrule 1x 2 0 AWG
Connecting Capacity UL/CSA:	Screw Clamp / Rigid 4 00 AWG Stranded 0 AWG
Connecting Capacity Main Circuit:	Screw Clamp / Flexible 1x 16 70 mm² Screw Clamp / Rigid 1x 16 95 mm² Screw Clamp / With Insulated Ferrrule 1x 50 mm²
Connection Type:	Screw clamp
Country of Origin:	France (FR)
Customs Tariff Number:	85369010
Data Sheet, Technical Information:	1SNC160019C0202
Declaration of Conformity - CE:	1SND225017U1000
Degree of Protection:	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Dielectric Test Voltage:	2200 V
EAC Certificate:	1SND161009A1100
EAN:	3472594007722
ETIM 4:	EC000901 - Ground terminal block
ETIM 5:	EC000901 - Ground terminal block
ETIM 6:	EC000901 - Ground terminal block
Environmental Information:	1SND220004E1002
Rammability According to UL94:	V0
Function:	Ground
Gauge Type:	B11
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SNC160019C0202
Insulation Material:	
Invoice Description:	D70/22.P Screw Clamp Terminal Blocks - Ground - Green-Yellow
Minimum Order Quantity:	10 piece
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Number of Levels:	1
Object Classification Code:	X

Order Multiple:	10 piece
Package Level 1 EAN:	3472594007722
Package Level 1 Gross Weight:	2.22 kg
Package Level 1 Height:	74 mm
Package Level 1 Length:	175 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	135 mm
Package Level 2 Height:	150 mm
Package Level 2 Length:	500 mm
Package Level 2 Units:	80 piece
Package Level 2 Width:	300 mm
Package Level 3 Units:	3840 piece
Pollution Degree:	3
Product Main Type:	D70/22.P
Product Name:	Terminal block
Product Net Depth:	68.8 mm
Product Net Height:	74 mm
Product Net Weight:	222 g
Product Net Width:	22 mm
Product Packing Type:	Box
Rated Cross-Section:	70 mm ²
Rated Impulse Withstand Voltage (U_{imp}):	8000 V
Rated Short-time Withstand Current (I_{cw}):	for 1 s 8400 A
Recommended Screw Driver:	6 mm
Resistance to Vibrations acc. to IEC 60068-2-6:	Compliant
Selling Unit of Measure:	piece
Spacing:	22 mm
Sub-Function:	2 connections
Sub-Function 2:	Screw rail connection
Sub-Function 3:	2 connections
Tightening Torque:	acc. IEC 60947-1 6 N·m Manufacturer 7 N·m
Wire Stripping Length:	25.0 mm
cUL Certificate:	1SND161001A0209

