D300/55.FF



Products Low Voltage Products and Systems Connection Devices Terminal Blocks SNA Series

| General Information | |
|------------------------|--|
| Extended Product Type: | D300/55.FF |
| Product ID: | 1SNA190005R2400 |
| EAN: | 3472591900057 |
| Catalog Description: | D300/55.FF Stud Terminal Block - Feed-through - Grey |
| Long Description: | - Rated cross section up to 300 mm2 / 1000 Kcmil, IP20 protection cover, - Holding foot on |
| | DIN 3 rail with two position for easy mounting, lug mounting in accordance with NF C 20-13 |
| | 0 and DIN 46234, various marking options, rail or base mounting. |

Additional Information

| ABB Industrial IT Suite: | Control IT |
|------------------------------------|--|
| Ambient Air Temperature: | Operation -55 +110 °C |
| | Storage -55 +110 °C |
| Ambient Temperature: | -5 +40 °C |
| Color: | Grey |
| Connecting Capacity UL/CSA: | Stranded 1000 AWG |
| Connecting Capacity Main Circuit: | Stud / Rigid 1x 6 300 mm² |
| Connection Type: | Stud |
| Country of Origin: | France (FR) |
| Customs Tariff Number: | 85369010 |
| Data Sheet, Technical Information: | 1SNC160019C0202 |
| Declaration of Conformity - CE: | 1SND225010U1000 |
| EAC Certificate: | 1SND161009A1100 |
| EAN: | 3472591900057 |
| ЕПМ 4: | EC000897 - Feed-through terminal block |
| ЕПМ 5: | EC000897 - Feed-through terminal block |
| ЕПМ 6: | EC000897 - Feed-through terminal block |
| Environmental Information: | 1SND220043E1002 |
| Rammability According to UL94: | V0 |
| Function: | Feed-through |
| IIT Publishing Status: | Level 0 - Information enabled |
| Industrial IT Certification Level: | 0 |
| Instructions and Manuals: | 1SNC160019C0202 |
| Insulation Material: | Polyamide |
| Invoice Description: | D300/55.FF Stud Terminal Block - Feed-through - Grey |
| Maximum Operating Voltage UL/CSA: | Main Circuit 600 V |
| Minimum Order Quantity: | 1 piece |
| Mounting on DIN Rail: | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Number of Levels: | 1 |
| Object Classification Code: | X |
| Order Multiple: | 1 piece |
| Package Level 1 EAN: | 3472591900057 |
| Package Level 1 Gross Weight: | 0.775 kg |
| Package Level 1 Height: | 57 mm |
| Package Level 1 Length: | 130 mm |
| Package Level 1 Units: | 1 piece |

| | • |
|--|---|
| Package Level 1 Width: | 163 mm |
| Package Level 2 Gross Weight: | 15.950 kg |
| Package Level 2 Height: | 150 mm |
| Package Level 2 Length: | 500 mm |
| Package Level 2 Units: | 20 piece |
| Package Level 2 Width: | 300 mm |
| Package Level 3 Units: | 480 piece |
| Pollution Degree: | 3 |
| Product Main Type: | D300/55.FF |
| Product Name: | Terminal Block |
| Product Net Depth: | 99 mm |
| Product Net Height: | 163 mm |
| Product Net Weight: | 775 g |
| Product Net Width: | 55 mm |
| Product Packing Type: | Box |
| Rated Cross-Section: | 300 mm ² |
| Rated Current (In): | Main Circuit 520 A |
| Rated Short-time Withstand Current (I _{cw}): | for 1 s 8000 A |
| Rated Voltage (U _r): | 1000 V |
| RoHS Date: | 20140212 |
| RoHS Information: | 1SND230022F0204 |
| RoHS Status: | Following EU Directive 2011/65/EC |
| Selling Unit of Measure: | piece |
| Short Description: | grey Power Terminal Blocks D300/55.FF 2 studs M16 |
| Spacing: | 55 mm |
| Sub-Function 3: | 2 connections |
| Tightening Torque: | Cable Lug 50 N·m Central Bolt 12 N·m |
| al II. Cortificato: | 1000465001400001 |

cUL Certificate:

1SND165001A0201

