

**W-Series
WQV 10/2**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com


Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | |
|------------|---|
| Type | WQV 10/2 |
| Order No. | 1052560000 |
| Version | W-Series, Cross-connector, For the terminals, No. of poles: 2 |
| GTIN (EAN) | 4008190154943 |
| Qty. | 50 pc(s). |

W-Series
WQV 10/2

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 7.55 mm | Width (inches) | 0.297 inch |
| Height | 16.9 mm | Height (inches) | 0.665 inch |
| Depth | 18 mm | Depth (inches) | 0.709 inch |
| Net weight | 3.6 g | | |

Temperatures

| | | | |
|----------------------------------|--------|----------------------------------|--------|
| Continuous operating temp., min. | -50 °C | Continuous operating temp., max. | 100 °C |
|----------------------------------|--------|----------------------------------|--------|

Material data

| | | | |
|---------------------------|-------|--------|--------|
| Material | PA 66 | Colour | Yellow |
| UL 94 flammability rating | V-2 | | |

System specifications

| | | | |
|---------|-------------------|---------------|------|
| Version | For the terminals | Mounting rail | none |
|---------|-------------------|---------------|------|

Additional technical data

| | | | |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | Screwed | | |

Cross-connector

| | | | |
|----------------------------------|-----------------|--|--------------|
| No. of cross-connected terminals | 2 | Rated current, 2-pole | 57 A |
| Rated current, multi-pole | 57 A | Tightening torque range for fixing screw | 0.5...1.0 Nm |
| Type | Cross-connector | | |

Dimensions

| | |
|-----------------|--------|
| Pitch in mm (P) | 9.9 mm |
|-----------------|--------|

Rating data

| | |
|---------------|------|
| Rated current | 76 A |
|---------------|------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000489 | ETIM 4.0 | EC000489 |
| ETIM 5.0 | EC000489 | ETIM 6.0 | EC000489 |
| UNSPSC | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Data sheet**W-Series
WQV 10/2**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

Technical data**Downloads**

| | |
|--------------------|---|
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | 1052560000_08873_WQV_10-2_STP.stp 08873_WQV_10-2_DXF.dxf |
| User Documentation | Beipackzettel_WQV.pdf |
