



### Main

|                           |  |
|---------------------------|--|
| Range                     | Acti 9   |
| Range of product          | Acti 9   |
| Product name              | Disbo iC60   |
| Product or component type | Miniature circuit-breaker  |
| Device short name         | IC60H  |
| Poles description         | 2P   |
| Number of protected poles | 2  |
| [In] rated current        | 16 A   |
| Network type              | AC   |
| Trip unit technology      | Thermal-magnetic   |
| Curve code                | C  |
| Breaking capacity code    | H  |
| Breaking capacity         | 15 kA Icu conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz<br>30 kA Icu conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz<br>42 kA Icu conforming to EN/IEC 60947-2 - 12...133 V AC 50/60 Hz<br>10 kA Icu conforming to EN/IEC 60947-2 - 100...133 V DC<br>10 kA Icu conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz<br>10000 A Icn conforming to EN/IEC 60898-1 - 415 V AC 50/60 Hz |
| Utilisation category      | Category A conforming to EN/IEC 60947-2  |

### Complementary

|                                       |  |
|---------------------------------------|--|
| Network frequency                     | 50/60 Hz   |
| [Ue] rated operational voltage        | 440 V AC 50/60 Hz  |
| Magnetic tripping limit               | 8 x In +/- 20 %  |
| [Ics] rated service breaking capacity | 5 kA 50 % x Icu conforming to EN/IEC 60947-2 - 440 V AC 50/60 Hz<br>10000 A 100 % x Icu conforming to EN/IEC 60898-1 - 415 V AC 50/60 Hz<br>7.5 kA 50 % x Icu conforming to EN/IEC 60947-2 - 380...415 V AC 50/60 Hz<br>21 kA 50 % x Icu conforming to EN/IEC 60947-2 - 12...133 V AC 50/60 Hz<br>10 kA 100 % x Icu conforming to EN/IEC 60947-2 - 100...133 V DC<br>15 kA 50 % x Icu conforming to EN/IEC 60947-2 - 220...240 V AC 50/60 Hz |
| Limitation class                      | 3 conforming to EN/IEC 60947-2   |

|  |   |
|--|---|
| [Ui] rated insulation voltage          | 500 V AC 50/60 Hz conforming to EN/IEC 60947-2  |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-2   |
| Contact position indicator             | Yes   |
| Control type                           | Toggle  |
| Local signalling                       | Trip indicator  |
| Mounting mode                          | Clip-on   |
| Mounting support                       | Rail  |
| Connection pitch                       | 18 mm Between phases  |
| 9 mm pitches                           | 4   |
| Height                                 | 85 mm   |
| Width                                  | 36 mm   |
| Depth                                  | 78.5 mm   |
| Product weight                         | 0.25 kg   |
| Colour                                 | White   |
| Mechanical durability                  | 20000 cycles  |
| Electrical durability                  | 10000 cycles  |
| Provision for padlocking               | Padlockable   |
| Connections - terminals                | Single terminal, top or bottom rigid wire(s) 1...25 mm <sup>2</sup> max<br>Single terminal, top or bottom flexible wire(s) 1...16 mm <sup>2</sup> max |
| Wire stripping length                  | 14 mm top or bottom   |
| Tightening torque                      | 2 N.m top or bottom   |
| Earth-leakage protection               | Separate block  |
| Compatibility code                     | IC60  |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Standards                             | EN/IEC 60947-2<br>EN/IEC 60898-1 |
| IP degree of protection               | IP20 conforming to IEC 60529     |
| Pollution degree                      | 3 conforming to EN/IEC 60947-2   |
| Tropicalisation                       | 2 conforming to IEC 60068-1      |
| Relative humidity                     | 95 % ( 55 °C )                   |
| Ambient air temperature for operation | -35...70 °C                      |
| Ambient air temperature for storage   | -40...85 °C                      |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 1310 - Schneider Electric declaration of conformity<br><a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>                |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |