

**SAK Series**  
**Q 4 DLI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Signal wiring**

Tailored and particularly compact: with our AIO initiator/actuator terminal blocks, you are relying on an application-optimised solution for signal wiring. We also offer you other terminal blocks featuring spring and screw connection technology for signal wiring.

**General ordering data**

|            |                                                                         |
|------------|-------------------------------------------------------------------------|
| Type       | Q 4 DLI                                                                 |
| Order No.  | <a href="#">1312700000</a>                                              |
| Version    | SAK Series, Cross-connector, for cross-connection link, No. of poles: 4 |
| GTIN (EAN) | 4008190162122                                                           |
| Qty.       | 50 pc(s).                                                               |

**SAK Series**  
**Q 4 DLI**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 23.3 mm | Width (inches)  | 0.917 inch |
| Height     | 4 mm    | Height (inches) | 0.157 inch |
| Depth      | 8 mm    | Depth (inches)  | 0.315 inch |
| Net weight | 2.747 g |                 |            |

**Material data**

|          |      |        |      |
|----------|------|--------|------|
| Material | CuSn | Colour | Grey |
|----------|------|--------|------|

**System specifications**

|               |                           |                                     |              |
|---------------|---------------------------|-------------------------------------|--------------|
| Version       | for cross-connection link | Tightening torque (cross-connector) | 0.4...0.8 Nm |
| Mounting rail | none                      |                                     |              |

**Additional technical data**

|                          |         |                     |                 |
|--------------------------|---------|---------------------|-----------------|
| Explosion-tested version | No      | Installation advice | Direct mounting |
| Type of fixing           | Screwed |                     |                 |

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 6.1 mm |
|-----------------|--------|

**Rating data**

|               |      |
|---------------|------|
| Rated current | 24 A |
|---------------|------|

**Classifications**

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 3.0   | EC000489    | ETIM 4.0   | EC000489    |
| ETIM 5.0   | EC000489    | ETIM 6.0   | EC000489    |
| UNSPSC     | 30-21-18-01 | eClass 5.1 | 27-14-11-40 |
| eClass 6.2 | 27-14-11-40 | eClass 7.1 | 27-14-11-40 |
| eClass 8.1 | 27-14-11-40 | eClass 9.0 | 27-14-11-40 |
| eClass 9.1 | 27-14-11-40 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                    |                                          |
|--------------------|------------------------------------------|
| Brochure/Catalogue | <a href="#">CAT 1 TERM 16/17 EN</a>      |
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a> |