



Main

| | |
|-----------------------------|---|
| Range | Spacial |
| Product name | Spacial SM |
| Product or component-type | Compact enclosure |
| Device application | Multi-purpose |
| Installation accessory-type | Floor-standing |
| Device composition | 1 body 1 cable gland plate 1 door 1 mounting plate 1 locking system with handle for door 4 mounting plate bracket |
| Removable parts | Door fixed by screws for hinge Mounting plate bracket fixed by screws Mounting plate fixed by screws for mounting plate-bracket |
| Enclosure nominal-height | 1400 mm |
| Enclosure nominal width | 800 mm |
| Enclosure nominal depth | 300 mm |

Complementary

| | |
|-----------------------------|--|
| Number of doors | 1 on front |
| Door opening side | Reversible 120 ° |
| Door type | Plain |
| Lock type | 4 points lock, handle with 5 mm double bar insert |
| Body type | Front part forming a rigid frame with welded corners Single piece body with welded rear panel |
| Mounting plate description | Plain |
| Type of gland plate | Standard |
| Cable entry | 1 entry |
| Material | Galvanised steel for mounting plate Sheet steel for body Sheet steel for door Zamak for hinge |
| Surface finish | Epoxy-polyester powder |
| Colour | Enclosure : grey RAL 7035 Handle : black RAL 9005 |
| Accessibility for operation | Front |

Environment

| | |
|-------------------------|------------------------------|
| Standards | IEC 62208 |
| Product certifications | BV UL DNV |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Product Life Status : **Commercialised**