

# PS1-3-2-65



Products → Low Voltage Products and Systems → Control Products → Manual Motor Starters  
→ Manual Motor Starters Accessories

## General Information

<b>Extended Product Type:</b>	PS1-3-2-65
<b>Product ID:</b>	1SAM201906R1123
<b>EAN:</b>	4013614400773
<b>Catalog Description:</b>	PS1-3-2-65 Busbar
<b>Long Description:</b>	PS1-3-2-65 3-phase busbar for 3 MS116 / MS132 with 2 HK/SK, I <sub>e</sub> =65A

## Ordering

<b>Minimum Order Quantity:</b>	1 piece
<b>Customs Tariff Number:</b>	85369010

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SBC100192C02--
<b>Instructions and Manuals:</b>	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
<b>Dimension Diagram:</b>	1SAM200450F0010

## Dimensions

<b>Product Net Width:</b>	167.5 mm
<b>Product Net Height:</b>	32.3 mm
<b>Product Net Depth / Length:</b>	13 mm
<b>Product Net Weight:</b>	0.067 kg

## Technical

<b>Rated Operational Voltage:</b>	690 V AC 250 V DC
<b>Rated Operational Current (I<sub>e</sub>):</b>	65 A
<b>Rated Impulse Withstand Voltage (U<sub>imp</sub>):</b>	6 kV
<b>Rated Short-time Withstand Current (I<sub>cw</sub>):</b>	100 kA
<b>Number of Phases:</b>	3
<b>Number of Poles:</b>	9
<b>Degree of Protection:</b>	IP20
<b>Pollution Degree:</b>	3

<b>Connection Type:</b>	Fork
<b>Standards:</b>	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
<b>Product Name:</b>	Busbar
<b>Suitable For:</b>	MS116 MS132
<b>Suitable for Product Class:</b>	Manual Motor Starter
<b>Accessory Group:</b>	Electrical
<b>Accessory Type:</b>	3-Phase Busbar

## Environmental

<b>Ambient Air Temperature:</b>	Operation -25 ... +70 °C Storage -50 ... +80 °C
<b>RoHS Status:</b>	Following EU Directive 2011/65/EU

## Technical UL/CSA

<b>Maximum Operating Voltage UL/CSA:</b>	Main Circuit 600 V AC
<b>Ampere Rating UL/CSA:</b>	65 A

## Certificates and Declarations (Document Number)

<b>cUL Certificate:</b>	1SAA963001-1701
<b>Declaration of Conformity - CE:</b>	1SAD938511-0056
<b>GOST Certificate:</b>	1SAA937000-2703
<b>Instructions and Manuals:</b>	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
<b>RoHS Information:</b>	1SAD938511-0056
<b>UL Certificate:</b>	1SAA963001-1602

## Container Information

<b>Package Level 1 Width:</b>	80 mm
<b>Package Level 1 Depth / Length:</b>	171 mm
<b>Package Level 1 Height:</b>	46 mm
<b>Package Level 1 Gross Weight:</b>	0.708 kg
<b>Package Level 1 EAN:</b>	4013614488153
<b>Package Level 1 Units:</b>	10 piece

## Classifications

<b>Object Classification Code:</b>	W
------------------------------------	---

<b>E-nummer:</b>	3111684
<b>ETIM 4:</b>	EC002498 - Accessories for low-voltage switch technology
<b>ETIM 5:</b>	EC000215 - Phase busbar
<b>ETIM 6:</b>	EC000215 - Phase busbar
<b>ETIM 7:</b>	EC000215 - Phase busbar
<b>eClass:</b>	7.0 27371306
<b>UNSPSC:</b>	39121521

