

PS1-5-2-65



Products → Low Voltage Products and Systems → Control Products → Manual Motor Starters
→ Manual Motor Starters Accessories

General Information

Extended Product Type:	PS1-5-2-65
Product ID:	1SAM201906R1125
EAN:	4013614400797
Catalog Description:	PS1-5-2-65 Busbar
Long Description:	PS1-5-2-65 3-phase busbar for 5 MS116 / MS132 with 2 HK/SK, I _e =65A

Ordering

Minimum Order Quantity:	1 piece
Customs Tariff Number:	85369010

Popular Downloads

Data Sheet, Technical Information:	1SBC100192C02--
Instructions and Manuals:	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
Dimension Diagram:	1SAM200450F0012

Dimensions

Product Net Width:	293.5 mm
Product Net Height:	32.3 mm
Product Net Depth / Length:	13 mm
Product Net Weight:	0.122 kg

Technical

Rated Operational Voltage:	690 V AC 250 V DC
Rated Operational Current (I_e):	65 A
Rated Impulse Withstand Voltage (U_{imp}):	6 kV
Rated Short-time Withstand Current (I_{cw}):	100 kA
Number of Phases:	3
Degree of Protection:	IP20
Pollution Degree:	3
Connection Type:	Fork

Standards:	IEC/EN 60947-1 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
-------------------	--

Product Name:	Busbar
----------------------	--------

Suitable For:	MS116 MS132
----------------------	----------------

Suitable for Product Class:	Manual Motor Starter
------------------------------------	----------------------

Accessory Group:	Electrical
-------------------------	------------

Accessory Type:	3-Phase Busbar
------------------------	----------------

Environmental

Ambient Air Temperature:	Operation -25 ... +70 °C Storage -50 ... +80 °C
---------------------------------	--

RoHS Status:	Following EU Directive 2011/65/EU
---------------------	-----------------------------------

Technical UL/CSA

Maximum Operating Voltage UL/CSA:	Main Circuit 600 V AC
--	-----------------------

Ampere Rating UL/CSA:	65 A
------------------------------	------

Certificates and Declarations (Document Number)

cUL Certificate:	1SAA963001-1701
-------------------------	-----------------

Declaration of Conformity - CE:	1SAD938511-0056
--	-----------------

GOST Certificate:	1SAA937000-2703
--------------------------	-----------------

Instructions and Manuals:	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802
----------------------------------	---

RoHS Information:	1SAD938511-0056
--------------------------	-----------------

UL Certificate:	1SAA963001-1602
------------------------	-----------------

Container Information

Package Level 1 Width:	80 mm
-------------------------------	-------

Package Level 1 Depth / Length:	297 mm
--	--------

Package Level 1 Height:	46 mm
--------------------------------	-------

Package Level 1 Gross Weight:	1.27 kg
--------------------------------------	---------

Package Level 1 EAN:	4013614488177
-----------------------------	---------------

Package Level 1 Units:	10 piece
-------------------------------	----------

Classifications

Object Classification Code:	W
------------------------------------	---

E-number:	3111686
------------------	---------

ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC000215 - Phase busbar
ETIM 6:	EC000215 - Phase busbar
ETIM 7:	EC000215 - Phase busbar
eClass:	7.0 27371306
UNSPSC:	39121521

