

**Industrial Ethernet
IE-FC-PWPC**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Type	IE-FC-PWPC
Order No.	1450820000
Version	FrontCom, Touch-safe protection
GTIN (EAN)	4050118255584
Qty.	1 pc(s).

**Industrial Ethernet
IE-FC-PWPC**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	47.5 mm	Length (inches)	1.87 inch
Width	47.5 mm	Width (inches)	1.87 inch
Height	45 mm	Height (inches)	1.772 inch
Net weight	19.18 g		

Temperatures

Operating temperature	Storage temperature
Installation temperature	

General data

Material	PC	Product type	Touch-safe protection
----------	----	--------------	-----------------------

Standards

Certificate No. (GERMLLOYD)	13866-15
-----------------------------	----------

Downloads

GL Approval Guidelines	GL_FrontCom.pdf
------------------------	-----------------

Classifications

ETIM 5.0	EC000456	ETIM 6.0	EC002498
UNSPSC	31-16-23-03	eClass 6.2	27-25-92-07
eClass 7.1	27-18-92-17	eClass 8.1	27-18-92-17
eClass 9.0	27-18-92-17	eClass 9.1	27-18-92-90

Approvals

Approvals	
ROHS	Conform

**Industrial Ethernet
IE-FC-PWPC**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

