



Main

Range of product	TeSys U
Range	TeSys
Device short name	LUL
Product or component type	Communication module
Product compatibility	LUCA LUCD LUCL LUCM LUCC LUCB

Complementary

Function available	Communication module
Mounting mode	Plug-in
Mounting location	Front side
Physical interface	9-way SUB-D female
Bus type	CANopen
Communication port protocol	CAN2.B CAN2.0A
Addressing	1...127
Current consumption	1.5 mA at 24 V DC 20...28 V
Logic input	Positive at 24 V DC - 7 mA
Response time	10 ms +/- 30 % change to state 1 10 ms +/- 30 % change to state 0
Input type	Resistive
Number of outputs	2 dedicated to starter-controller coil operation 1
[Us] rated supply voltage	24 V DC
Output current	<= 500 mA
Protection type	GL fuse 2 A

Switching current capacity	0.5 mA at 24 V
Local signalling	3 LEDs front panel
Connection pitch	3.81 mm
Connections - terminals	Screw clamp terminals 2 cable 0.25...0.34 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.14...0.75 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.14...1 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.25...1 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 2 cable 0.14...0.5 mm ² - cable stiffness: rigid - without cable end Screw clamp terminals 1 cable 0.25...0.5 mm ² - cable stiffness: flexible - with cable end
Associated cable type	AWG 26...AWG 16
Tightening torque	0.2...0.25 N.m - with screwdriver 2.5 mm
Compatibility code	LUL

Environment

Standards	DR 303-2 CIADS-301 V4.02
Ambient air temperature for operation	-25...55 °C

Contractual warranty

Warranty period	18 months
-----------------	-----------