

LC1D80B7

TeSys D contactor - 3P(3 NO) - AC-3 - <= 440 V
80 A - 24 V AC 50/60 Hz coil



Main

| | |
|--|---|
| Range of product | TeSys D |
| Range | TeSys |
| Product name | TeSys D |
| Product or component type | Contactor |
| Device short name | LC1D |
| Contactor application | Motor control Resistive load |
| Utilisation category | AC-3 AC-1 |
| Poles description | 3P |
| Pole contact composition | 3 NO |
| [Ue] rated operational voltage | <= 300 V DC 25...400 Hz for power circuit <= 690 V AC for power circuit |
| [Ie] rated operational current | 125 A (<= 60 °C) at <= 440 V AC AC-1 for power circuit 80 A (<= 60 °C) at <= 440 V AC AC-3 for power circuit |
| Motor power kW | 22 kW at 220...230 V AC 50/60 Hz 45 kW at 415...440 V AC 50/60 Hz 55 kW at 500 V AC 50/60 Hz 45 kW at 660...690 V AC 50/60 Hz 45 kW at 1000 V AC 50/60 Hz 37 kW at 380...400 V AC 50/60 Hz |
| Motor power hp | 15 hp at 230/240 V AC 50/60 Hz for 1 phase motors 60 hp at 460/480 V AC 50/60 Hz for 3 phases motors 25 hp at 230/240 V AC 50/60 Hz for 3 phases motors 20 hp at 200/208 V AC 50/60 Hz for 3 phases motors 60 hp at 575/600 V AC 50/60 Hz for 3 phases motors 7.5 hp at 115 V AC 50/60 Hz for 1 phase motors |
| Control circuit type | AC 50/60 Hz |
| Control circuit voltage | 24 V AC 50/60 Hz |
| Auxiliary contact composition | 1 NO + 1 NC |
| [Uimp] rated impulse withstand voltage | Conforming to IEC 60947 |
| Overtoltage category | III |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|--|--|
| [I _{th}] conventional free air thermal current | 125 A at ≤ 60 °C for power circuit 10 A at ≤ 60 °C for signalling circuit |
| I _{rms} rated making capacity | 1100 A at 440 V for power circuit conforming to IEC 60947 250 A DC for signalling circuit conforming to IEC 60947-5-1 140 A AC for signalling circuit conforming to IEC 60947-5-1 |
| Rated breaking capacity | 1100 A at 440 V for power circuit conforming to IEC 60947 |
| [I _{cw}] rated short-time withstand current | 120 A 500 ms signalling circuit 135 A ≤ 40 °C 10 min power circuit 140 A 100 ms signalling circuit 320 A ≤ 40 °C 1 min power circuit 640 A ≤ 40 °C 10 s power circuit 990 A ≤ 40 °C 1 s power circuit 100 A 1 s signalling circuit |
| Associated fuse rating | 160 A gG at ≤ 690 V coordination type 2 for power circuit 200 A gG at ≤ 690 V coordination type 1 for power circuit 10 A gG for signalling circuit conforming to IEC 60947-5-1 |
| Average impedance | 0.8 mΩ at 50 Hz - I _{th} 125 A for power circuit |
| [U _i] rated insulation voltage | 690 V for signalling circuit conforming to IEC 60947-1 600 V for signalling circuit certifications CSA 600 V for power circuit certifications UL 600 V for signalling circuit certifications UL 600 V for power circuit certifications CSA 1000 V for power circuit conforming to IEC 60947-4-1 |
| Electrical durability | 0.8 Mcycles 125 A AC-1 at U _e ≤ 440 V 1.5 Mcycles 80 A AC-3 at U _e ≤ 440 V |
| Power dissipation per pole | 5.1 W AC-3 12.5 W AC-1 |
| Protective cover | With |
| Mounting support | Rail Plate |
| Standards | EN 60947-5-1 IEC 60947-4-1 EN 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Product certifications | CSA UL GL GOST LROS RINA CCC BV DNV |
| Connections - terminals | Control circuit : screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end Power circuit : connector 1 cable(s) 4...50 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit : screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end Power circuit : connector 1 cable(s) 4...50 mm ² - cable stiffness: solid - without cable end Power circuit : connector 2 cable(s) 4...25 mm ² - cable stiffness: solid - without cable end Control circuit : screw clamp terminals 1 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Power circuit : connector 2 cable(s) 4...16 mm ² - cable stiffness: flexible - with cable end Power circuit : connector 2 cable(s) 4...25 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: solid - without cable end Power circuit : connector 1 cable(s) 4...50 mm ² - cable stiffness: flexible - without cable end Control circuit : screw clamp terminals 2 cable(s) 1...4 mm ² - cable stiffness: flexible - without cable end |
| Tightening torque | Control circuit : 1.2 N.m - on screw clamp terminals - with screwdriver Philips No 2 Power circuit : 9 N.m - on connector hexagonal 4 mm Power circuit : 9 N.m - on connector - with screwdriver flat Ø 6 to Ø 8 mm Control circuit : 1.2 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm |
| Operating time | 20...35 ms closing 6...20 ms opening |
| Safety reliability level | B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1 B10d = 20000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1 |

| | |
|-----------------------|------------------------|
| Mechanical durability | 4 Mcycles |
| Operating rate | 3600 cyc/h at <= 60 °C |

Complementary

| | |
|---------------------------------|--|
| Coil technology | Without built-in suppressor module |
| Control circuit voltage limits | 0.3...0.6 Uc drop-out at 55 °C, AC 50/60 Hz 0.85...1.1 Uc operational at 55 °C, AC 60 Hz 0.8...1.1 Uc operational at 55 °C, AC 50 Hz |
| Inrush power in VA | 245 VA at 20 °C (cos ϕ 0.75) 60 Hz 245 VA at 20 °C (cos ϕ 0.75) 50 Hz |
| Hold-in power consumption in VA | 26 VA at 20 °C (cos ϕ 0.3) 60 Hz 26 VA at 20 °C (cos ϕ 0.3) 50 Hz |
| Heat dissipation | 6...10 W at 50/60 Hz |
| Auxiliary contacts type | Type mirror contact (1 NC) conforming to IEC 60947-4-1 Type mechanically linked (1 NO + 1 NC) conforming to IEC 60947-5-1 |
| Signalling circuit frequency | 25...400 Hz |
| Minimum switching current | 5 mA for signalling circuit |
| Minimum switching voltage | 17 V for signalling circuit |
| Non-overlap time | 1.5 ms on de-energisation (between NC and NO contact) 1.5 ms on energisation (between NC and NO contact) |
| Insulation resistance | > 10 MOhm for signalling circuit |
| Contact compatibility | M11 |
| Compatibility code | LC1D |

Environment

| | |
|---|---|
| IP degree of protection | IP2x front face conforming to IEC 60529 |
| Protective treatment | TH conforming to IEC 60068-2-30 |
| Pollution degree | 3 |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -60...80 °C |
| Permissible ambient air temperature around the device | -40...70 °C at Uc |
| Operating altitude | 3000 m without derating in temperature |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Vibrations contactor closed 3 Gn, 5...300 Hz Shocks contactor open 8 Gn for 11 ms Vibrations contactor open 2 Gn, 5...300 Hz Shocks contactor closed 10 Gn for 11 ms |
| Height | 127 mm |
| Width | 85 mm |
| Depth | 130 mm |
| Product weight | 1.59 kg |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0701 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product environmental |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
