

# LOCKNUTS WITH COLLAR 1142

*Polyamide PA6.6*


Pg thread DIN 40 430 - Dimensions DIN 46 320



# LOCKNUTS WITH COLLAR 1142

## *Technical characteristics*

Material (Body)	Polyamide PA6.6
UL94 class	V2
Min operating temperature range	-20 °C
Max operating temperature range	90 °C



## LOCKNUTS WITH COLLAR **1142**

*List of products*

# 1142



Type	P	ØA	B	H	Pack qty	Min. pack qty	Colour
1142007	Pg7	21 mm	19 mm	5 mm	100	100	Grey RAL 7035
1142009	Pg9	24 mm	22 mm	5 mm	700	100	Grey RAL 7035
1142011	Pg11	26 mm	24 mm	5 mm	500	100	Grey RAL 7035
1142013	Pg13,5	29 mm	27 mm	6 mm	400	100	Grey RAL 7035
1142016	Pg16	33 mm	30 mm	6 mm	100	100	Grey RAL 7035
1142021	Pg21	39 mm	36 mm	7 mm	200	50	Grey RAL 7035
1142029	Pg29	50 mm	46 mm	7 mm	50	50	Grey RAL 7035
1142036	Pg36	66 mm	60 mm	8 mm	30	30	Grey RAL 7035
1142042	Pg42	73 mm	65 mm	8 mm	25	25	Grey RAL 7035
1142048	Pg48	78 mm	70 mm	8 mm	20	20	Grey RAL 7035
1142007G	Pg7	21 mm	19 mm	5 mm	100		Dark Grey RAL 7001
1142009G	Pg9	24 mm	22 mm	5 mm	700	100	Dark Grey RAL 7001
1142011G	Pg11	26 mm	24 mm	5 mm	500	100	Dark Grey RAL 7001
1142013G	Pg13,5	29 mm	27 mm	6 mm	400	100	Dark Grey RAL 7001
1142016G	Pg16	33 mm	30 mm	6 mm	100	100	Dark Grey RAL 7001
1142021G	Pg21	39 mm	36 mm	7 mm	200	50	Dark Grey RAL 7001
1142029G	Pg29	50 mm	46 mm	7 mm	50	50	Dark Grey RAL 7001
1142036G	Pg36	66 mm	60 mm	8 mm	30		Dark Grey RAL 7001
1142042G	Pg42	73 mm	65 mm	8 mm	25	25	Dark Grey RAL 7001
1142048G	Pg48	78 mm	70 mm	8 mm	20	20	Dark Grey RAL 7001
1142007N	Pg7	21 mm	19 mm	5 mm	100		Black RAL 9005
1142009N	Pg9	24 mm	22 mm	5 mm	700	100	Black RAL 9005
1142011N	Pg11	26 mm	24 mm	5 mm	500	100	Black RAL 9005
1142013N	Pg13,5	29 mm	27 mm	6 mm	400	100	Black RAL 9005
1142016N	Pg16	33 mm	30 mm	6 mm	100	100	Black RAL 9005
1142021N	Pg21	39 mm	36 mm	7 mm	200	50	Black RAL 9005
1142029N	Pg29	50 mm	46 mm	7 mm	50	50	Black RAL 9005
1142036N	Pg36	66 mm	60 mm	8 mm	30	30	Black RAL 9005
1142042N	Pg42	73 mm	65 mm	8 mm	25	25	Black RAL 9005
1142048N	Pg48	78 mm	70 mm	8 mm	20	20	Black RAL 9005