



Main

| | |
|-------------------------------|------------------------------------|
| Range | TeSys |
| Product name | TeSys VARIO |
| Device short name | VCD |
| Product or component type | Emergency stop switch disconnecter |
| Performance level | High performance |
| Poles description | 3P |
| Contacts type and composition | 3 NO |
| Network type | DC AC |
| Control type | Rotary handle |
| Rotary handle mounting style | Direct |
| Handle colour | Red |
| Handle front plate colour | Yellow |
| Suitability for isolation | Yes |

Complementary

| | |
|--|------------------------------|
| Rotary handle padlocking | 1 to 3 padlocks 4...8 mm |
| Marking | 0 - 1 |
| Mounting support | Handle: door Switch: door |
| Fixing mode | Hole with 22.5 mm for handle |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 8 kV |
| [Ith] conventional free air thermal current | 32 A |
| [Ithe] conventional enclosed thermal current | 25 A |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| [I _e] rated operational current | 21.8 A AC-23 U _e : 400 V |
| Rated operational power in W | 11 kW at 500 V (AC-23A) 15 kW at 690 V (AC-23A) 7.5 kW at 500 V (AC-3) 7.5 kW at 690 V (AC-3) 1.5 kW at 230...240 V (AC-3) 5.5 kW at 230...240 V (AC-23A) 11 kW at 400...415 V (AC-23A) 7.5 kW at 400...415 V (AC-3) |
| Intermittent duty class | 30 |
| Making capacity (I Rms) | 320 A at 400 V AC-21A 320 A at 400 V AC-22A 320 A at 400 V AC-23A |
| [I _{cm}] rated short-circuit making capacity | 1 kA at 400 V at I _{peak} |
| [I _{cw}] rated short-time withstand Rms current | 384 A at 400 V duration: 1 s |
| Rated conditional short-circuit current | 10 kA at 400 V - associated fuse 35 A aM 10 kA at 400 V - associated fuse 35 A gG |
| Breaking capacity | 250 A at 400 V (AC-21A) 250 A at 400 V (AC-22A) 250 A at 400 V (AC-23A) |
| Device composition | Switch Handle |
| Mechanical durability | 100000 cycles |
| Electrical durability | 100000 cycles AC-21 30000 cycles DC-1...5 |
| Connections - terminals | Power circuit: screw clamp terminals 10 mm ² - solid Power circuit: screw clamp terminals 6 mm ² - flexible - with cable end |
| Tightening torque | Power circuit: 2.1 N.m - on screw clamp terminals |
| Handle front plate dimension | 60 x 60 mm |
| Height | 74 mm |
| Width | 60 mm |
| Net weight | 0.215 kg |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC 60947-3 |
| Product certifications | GL CCC CSA UL |
| Protective treatment | TC |
| IP degree of protection | IP20 conforming to IEC 60529 IP65 |
| Mechanical robustness | Vibrations 10...150 Hz (1 gn) conforming to IEC 60068-2-6 Shocks 11 ms (30 Gn) conforming to IEC 60068-2-27 |
| Ambient air temperature for operation | -20...50 °C |
| Fire resistance | 960 °C conforming to IEC 60695-2-1 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 223 g |
| Package 1 Height | 7.8 cm |
| Package 1 width | 8.4 cm |
| Package 1 Length | 12.1 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 24 |
| Package 2 Weight | 5.834 kg |

| | |
|------------------------------|----------|
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 192 |
| Package 3 Weight | 57.02 kg |
| Package 3 Height | 80 cm |
| Package 3 width | 80 cm |
| Package 3 Length | 60 cm |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free | Yes |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|