

# Accessory

## Surge unit



It absorbs the surge arisen out of the coil of the contactor.



It can be installed simply to the contactor.

- Rated operation voltage (Ue): AC 24 ~ 440V / DC 24 ~ 125V
- Rated insulation voltage (Ui): 1000V
- Rated impulse withstand voltage (Uimp): 8kV
- Degree of protection: IP20
- Combination with 3Pole 6a/3~150a/3, 4Pole 32a/4~85a/4

### US Type

Surge unit		Rated voltage	Internal elements spec.			Contactor
Type	Composition		V	R	C	
US-1	Varistor+RC	AC	24~48V	120V	100Ω	0.1μF
US-2	Varistor+RC		100~125V	270V	100Ω	0.1μF
US-3	Varistor+RC		200~240V	470V	100Ω	0.1μF
US-4	Varistor+RC	DC	24~48V	120V	100Ω	0.47μF
US-5	Varistor+RC		100~125V	270V	100Ω	0.47μF
US-6	Varistor+RC		200~220V	470V	100Ω	0.47μF
US-11	Varistor	AC/DC common	24~48V	120V	-	-
US-12	Varistor		100~125V	270V	-	-
US-13	Varistor		200~240V	470V	-	-
US-14	Varistor		380~440V	1000V	-	-
US-22	RC	AC	100~125V	-	56Ω	1μF

### Installation (US Type)





Connect the lead wires to the coil terminals of the contactor first. And then insert the body into the space of the contactor as shown above.

### AS Type

Surge unit		Rated voltage	Internal elements spec.			Contactor
Type	Composition		V	R	C	
AS-1	Varistor+RC	AC	24~48V	120V	100Ω	0.1μF
AS-2	Varistor+RC		100~125V	270V	100Ω	0.1μF
AS-3	Varistor+RC		200~240V	470V	100Ω	0.1μF
AS-4	Varistor+RC	DC	24~48V	120V	100Ω	0.47μF
AS-5	Varistor+RC		100~125V	270V	100Ω	0.47μF
AS-6	Varistor+RC		200~220V	470V	100Ω	0.47μF
AS-11	Varistor	AC/DC common	24~48V	120V	-	-
AS-12	Varistor		100~125V	270V	-	-
AS-13	Varistor		200~240V	470V	-	-
AS-14	Varistor		380~440V	1000V	-	-

### Specification of surge unit

Without surge unit	① With Varistor unit	② With CR+Varistor unit
Surge voltage, arise when the coil is off, may provoke mis-operation and damage in the circuit. 	Varistor has an effect to cut down the peak voltage. 	Varistor has an effect to cut down the peak voltage and high frequency wave. 