

# LEGENDS MG-TAR

*precut*

MG-TAR legends are often designed to fit particular components with a suitable clip-in or stickon location. Consult us for availability of other colours.



CERTIFICATES 

  2011/65/EU

LABORATORY TEST 

## **CEI EN 60950-1**

### **INDELIBILITY**

#### **Information technology equipment - Safety**

*Part 1: General requirements*

*§ 1.7.11 Durability*

Compliance is checked by inspection and by rubbing the marking by hand for 15 s with a piece of cloth soaked with water and again for 15 s with a piece of cloth soaked with hexane.

After this test, the marking shall be legible; it shall not be possible to remove marking plates easily and they shall show no curling.

## **CEI EN 61010-1**

### **INDELIBILITY**

#### **Ed.2 equivalent to VDE 0411-1**

#### **Safety indications for electric devices for measurement, control and laboratory use**

*Part 1: General indications*

This regulation requires that both material and the print shall withstand, cleaning with chemical agents commonly used in industry.

By rubbing manually by hand, without excessive pressure, for 30 seconds with a cloth soaked in the specific detergent or, if not specified, Isopropyl Alcohol.

---

## **CEMBRE STANDARD**

### **INDELIBILITY**

This test was created to simulate cleaning with chemical products commonly used on various surfaces.

By wiping with a cloth soaked in 95% Ethanol 30 times and making a visual inspection after every 10 passes.

---

## **DIN 30643**

---

## LEGENDS MG-TAR

### *Technical characteristics*

Min operating temperature range	-30 °C
Max operating temperature range	80 °C
UL94 class	V0
Material	Rigid PVC
Precut	yes
Geometric shape	rectangular with square corners



## LEGENDS MG-TAR

### List of products

MG-TAR						
Type	Height	Length	Quantity per sheet	Pack qty	SWcode	Colour
45044	17 mm	40 mm	12	600	712	Yellow
45491	17 mm	140 mm	6	300	839	White
45492	40 mm	140 mm	2	100	877	White
45390	14 mm	45.5 mm	14	700	718	White
45090	6 mm	60 mm	16	800	169	White
45396	6.3 mm	30 mm	45	2	800	White
45394	6.3 mm	44 mm	30	750	798	White
45344	6.3 mm	44 mm	30	750	798	Yellow
45384GY	6.3 mm	44 mm	30	750	798	Grey
45324	6.3 mm	44 mm	30	750	798	Red
45364	6.3 mm	44 mm	30	750	798	Blue
45098	7.5 mm	40 mm	24	1,200	801	White
45048	7.5 mm	40 mm	24	1,200	801	Yellow
45089	8 mm	55 mm	24	1	719	White
45395	10 mm	28.5 mm	27	1,350	350	White
45297	10.4 mm	21 mm	50	1,250	351	White
45392	12 mm	57.5 mm	16	800	708	White
45192	14 mm	84 mm	6	300	805	White
45142	14 mm	84 mm	6	300	805	Yellow
45194	17 mm	35 mm	18	900	711	White
45144	17 mm	35 mm	18	900	711	Yellow
45094N	17 mm	40 mm	18	900	713	White
45044N	17 mm	40 mm	18	900	713	Yellow
45064N	17 mm	40 mm	18	900	713	Blue
45195	17 mm	44 mm	12	600	717	White
45145	17 mm	44 mm	12	600	717	Yellow
45391	17.5 mm	36 mm	18	900	709	White
45490	8.5 mm	30 mm	33	1,650	720	White