

TRANSPARENT HOLDERS PM-03

for cable tags 4 mm

□

PM holders are profiled to allow each type to accommodate a range of cable sizes.

TRANSPARENT HOLDERS PM-03

Technical characteristics

Dimensional form	Transparent holder
Material	Plasticised transparent PVC
UL94 class	V0
Min operating temperature range	-40 °C
Max operating temperature range	80 °C
Minimum outside diameter	4 mm
Maximum outside diameter	6.3 mm
Minimum section	4 mm ²
Maximum section	10 mm ²

□□□□

TRANSPARENT HOLDERS PM-03

List of products

PM-03

- - | Type | Length | Pack qty | |
|-------|---------|----------|---|
| 50300 | 10 mm | 3,000 | □ |
| 50302 | 10 mm | 1,000 | □ |
| 50310 | 12 mm | 2,000 | □ |
| 50312 | 12 mm | 500 | □ |
| 50320 | 15 mm | 2,000 | □ |
| 50322 | 15 mm | 500 | □ |
| 50330 | 18 mm | 1,000 | □ |
| 50340 | 21 mm | 1,000 | □ |
| 50350 | 23 mm | 1,000 | □ |
| 50360 | 27 mm | 1,000 | □ |
| 50370 | 30 mm | 500 | □ |
| 50380 | 1000 mm | 10 | □ |