

TRANSPARENT HOLDERS PM-02

for cable tags 4 mm

□

PM holders are profiled to allow each type to accommodate a range of cable sizes.

TRANSPARENT HOLDERS PM-02

Technical characteristics

Dimensional form	Transparent holder
Material	Plasticised transparent PVC
UL94 class	V0
Min operating temperature range	-40 °C
Max operating temperature range	80 °C
Minimum outside diameter	3.5 mm
Maximum outside diameter	4.3 mm
Minimum section	2.5 mm ²
Maximum section	4 mm ²

□ □ □

TRANSPARENT HOLDERS PM-02

List of products

PM-02

- - | Type | Length | Pack qty | |
|-------|---------|----------|---|
| 50200 | 10 mm | 4,000 | □ |
| 50202 | 10 mm | 1,000 | □ |
| 50210 | 12 mm | 4,000 | □ |
| 50212 | 12 mm | 1,000 | □ |
| 50220 | 15 mm | 3,000 | □ |
| 50222 | 15 mm | 1,000 | □ |
| 50230 | 18 mm | 2,000 | □ |
| 50240 | 21 mm | 2,000 | □ |
| 50250 | 23 mm | 2,000 | □ |
| 50260 | 27 mm | 1,000 | □ |
| 50270 | 30 mm | 1,000 | □ |
| 50280 | 1000 mm | 10 | □ |