

Contactors

Metasol MC 4P 18 to 85A

MC type Magnetic Contactors



Frame size		18AF			
Type	Screw clamp terminal	MC-6a/4	MC-9a/4	MC-12a/4	MC-18a/4
Number of poles	4pole				
Rated operational voltage (Ue)	690V				
Rated insulation voltage (Ui)	690V				
Rated frequency	50/60Hz				
Rated impulse withstand voltage, Uimp	6kV				
Maximum operating rate in operating cycles per hour(AC1)	1800 operations per hour				
Durability	Mechanical	15 mil. operations			
	Electrical	0.5 mil. operations		0.8 mil. operations	
Current	Thermal current A	25	25	25	40
and Power	AC-1 200/240V kW	9	9	9	15
	A	25	25	25	40
	380/400V kW	17	17	17	27
	A	25	25	25	40
	500/550V kW	21	21	21	35
	A	25	25	25	40
	690V kW	27	27	27	44
	A	25	25	25	40
UL rating	Continuous current A	25	25	25	32
(50/60Hz)	Single 110~120V HP	0.5	0.5	0.75	1
	Phase 220~240V HP	1.5	1.5	2	3
	Three 200~208V HP	2	2	3	7.5
	Phase 220~240V HP	3	3	5	7.5
	440~480V HP	5	5	7.5	10
	550~600V HP	7.5	7.5	10	15
Size and weight	AC Weight kg	0.33			
	Control Size(W×H×D) mm	45×73.5×80.4			
	DC Weight kg	0.4			
	Control Size(W×H×D) mm	45×73.5×96.6			
Auxiliary(standard)		-			
Auxiliary	Side Mount	UA-1			
	Front Mount	UA-2, UA-4			





22AF	40AF		85AF			
MC-22a/4	MC-32a/4	MC-40a/4	MC-50a/4	MC-65a/4	MC-75a/4	MC-85a/4
•	•	•	•	•	•	•
4pole	4pole			4pole		
690V	690V			690V		
690V	690V			1000V		
50/60Hz	50/60Hz			50/60Hz		
6kV	6kV			8kV		
1800 operations per hour	1800 operations per hour			1800 operations per hour		
15 mil. operations	15 mil. operations			12 mil. operations		
1 mil. operations	1 mil. operations			1 mil. operations		
40	50	60	80	100	110	135
15	18	22	30	37	41	51
40	50	60	80	100	110	135
27	35	42	56	70	76	95
40	50	60	80	100	110	135
35	43	52	70	88	97	120
40	50	60	80	100	110	135
44	55	66	88	110	120	150
40	50	60	80	100	110	135
32	45	50	70	80	90	100
2	2	3	3	5	5	7.5
3	5	5	7.5	10	15	15
7.5	7.5	10	10	15	20	25
7.5	10	10	15	20	25	30
10	20	25	30	40	50	50
15	20	25	30	40	50	50
0.4	0.59			1.2		
47.2×80×86.8	59×83.5×94.5			91×123.5×117.8		
0.5	0.7			1.29		
47.2×80×113.2	59×83.5×121			91×123.5×117.8		
-	-			-		
AU-1	AU-1			AU-1		
UA-2, UA-4	UA-2, UA-4			UA-2, UA-4		

Contactors

Metasol MC 4P 225 to 800A

MC type Magnetic Contactors



Frame size		225AF				
Type	Screw clamp terminal	MC-100a/4 MC-130a/4 MC-150a/4 MC-185a/4 MC-225a/4				
Number of poles		● ● ● ● ●				
Rated operational voltage (Ue)		4pole				
Rated insulation voltage (Ui)		690V				
Rated frequency		1000V				
Rated impulse withstand voltage, Uimp		50/60Hz				
Maximum operating rate in operating cycles per hour(AC1)		8kV				
Durability	Mechanical	1200 operations per hour				
	Electrical	5 mil. operations				
Current	Thermal current A	200	250	275	300	350
and Power	AC-1 200/240V kW	57	60	76	87	100
	A	200	250	275	300	350
	380/400V kW	106	110	142	165	185
	A	200	250	275	300	350
	500/550V kW	132	137	180	205	230
	A	200	250	275	300	350
	690V kW	165	170	225	255	290
	A	200	250	275	300	350
UL rating	Continuous current A	200	250	275	300	350
(50/60Hz)	Single 110~120V HP	7.5	10	15	15	15
	Phase 220~240V HP	15	20	25	30	40
	Three 200~208V HP	30	40	40	60	60
	Phase 220~240V HP	30	40	50	60	75
	440~480V HP	60	75	100	125	150
	550~600V HP	60	75	100	125	150
Size and weight	AC Weight kg	5.6				
	Control Size(W×H×D) mm	175×203×185				
	DC Weight kg					
	Control Size(W×H×D) mm					
Auxiliary(standard)		2NO2NC				
Auxiliary	Side Mount	AU-100 / AU-100E				
	Front Mount	-				

* - FLA = 722 A, LRA = 5618 A

** - FLA = 566 A, LRA = 4495 A



400AF			800AF		
MC-265a/4	MC-330a/4	MC-400a/4	MC-500a/4	MC-630a/4	MC-800a/4
•	•	•	•	•	•
4pole				4pole	
690V				690V	
1000V				1000V	
50/60Hz				50/60Hz	
8kV				8kV	
1200 operations per hour				1200 operations per hour	
2.5 mil. operations				2.5 mil. operations	
0.5 mil. operations				0.5 mil. operations	
400	500	520	700	900	1050
115	135	160	245	255	310
400	500	520	700	900	1050
215	250	300	450	470	570
400	500	520	700	900	1050
265	315	375	560	590	710
400	500	520	700	900	1050
335	390	470	710	740	900
400	500	520	700	900	1050
400	500	520	700	900	1050
-	-	-	-	-	-
-	-	-	-	-	-
75	100	125	150	200	200
100	125	150	200	250	300
200	200	300	400	500	600 *
200	200	300	400	500	600 **
9.9			26.3		
206×243×205			346×310 ×244		

2NO2NC	2NO2NC
AU-100	AU-100
-	-