



### Main

Range of product	Altivar
Product or component type	Communication module

### Complementary

Range compatibility	Altivar Process Modular Altivar Machine ATV340 except Sercos drives Altivar Machine ATV320 Altivar Process ATV900 Altivar 32 Lexium 32
Product compatibility	Lexium 32
Communication port protocol	EtherCAT
Electrical connection	2 connectors RJ45
Transmission rate	100 Mbps
Maximum cable distance between devices	100 M for 100 Mbps
Addressing	Logical addressing Node addressing Position addressing
Communication service	PDO and SDO support Drive profile CiA 402 velocity mode conforming to IEC 61800-7-201 (CiA 402) CANopen over EtherCAT (CoE)
Display type	1 LED for input status 1 LED for RUN 1 LED for error 1 LED for output status

### Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	56 G
Package 1 Height	4.5 Cm
Package 1 width	6.3 Cm
Package 1 Length	9 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**