



Main

| | |
|---------------------------|---|
| Range | TeSys |
| Product name | TeSys LE |
| Device short name | LE1D |
| Product or component type | Enclosed DOL starter |
| Device application | Standard |
| Utilisation category | AC-3 |
| Device composition | Thermal overload relay ordered separately Contactor |
| Control type | Push-button start green I Push-button stop/reset red O |

Complementary

| | |
|--|--|
| [Ie] rated operational current | 9 A AC-3 |
| Motor power kW | 4 kW at 380/400 V AC 50/60 Hz 4 kW at 415 V AC 50/60 Hz 4 kW at 440 V AC 50/60 Hz 2.2 kW at 220/230 V AC 50/60 Hz 5.5 kW at 500 V AC 50/60 Hz 5.5 kW at 660/690 V AC 50/60 Hz |
| [Ithe] conventional enclosed thermal current | 9 A |
| [Uc] control circuit voltage | 220 V AC 50/60 Hz |
| Cable entry number | 2 ISO20 top 2 ISO20 bottom 2 Pg 13 bottom 2 Pg 16 bottom |
| Width | 88 mm |
| Height | 166 mm |
| Depth | 128.5 mm |
| Net weight | 0.92 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Material | Polycarbonate |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -5...40 °C |
| Environmental characteristic | Standard environment |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 884 g |
| Package 1 Height | 15 cm |
| Package 1 width | 17.4 cm |
| Package 1 Length | 20.6 cm |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 1 |
| Package 2 Weight | 884 g |
| Package 2 Height | 18 cm |
| Package 2 width | 15.5 cm |
| Package 2 Length | 21.5 cm |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 30 |
| Package 3 Weight | 39.52 kg |
| Package 3 Height | 80 cm |
| Package 3 width | 80 cm |
| Package 3 Length | 60 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| RECh Regulation | RECh Declaration |
| RECh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|