

I : for short-circuit protection (magnetic)

trip unit MA12.5 for ComPacT NSX

### Complementary

Poles description

**Protection type** 

Trip unit rating

Network type

**Network frequency** 

Protected poles description

Trip unit protection functions

[Ue] rated operational voltage

Circuit breaker mounting mode

3t

12.5 A at 65 °C

50/60 Hz

Fixed

690 V AC 50/60 Hz

Instantaneous protection pick- up adjustment type li	Adjustable 9 settings
[li] instantaneous protection pick-up adjustment range	614 x ln
Farth-leakage protection	Without

### **Environment**

Standards	EN/IEC 60947-2 UL 508
Product certifications	EAC CCC Marine
Pollution degree	3 conforming to IEC 60947-1

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	414.0 g
Package 1 Height	7 cm
Package 1 width	10 cm
Package 1 Length	11.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	28
Package 2 Weight	11.956 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

# Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

# Contractual warranty

Warranty	18 months
----------	-----------