



# trip unit MA100 for ComPacT NSX 100/160/250 circuit breakers, magnetic, rating 100 A, 3 poles 3d

# Main

Range	ComPacT new generation
Range of product	ComPacT NSX100250 new generation
Product or component type	Trip unit
Trip unit name	MA
Trip unit technology	Magnetic
Range compatibility	ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX250
Device application	Motor
Poles description	3P
Protected poles description	3t
Trip unit protection functions	
Protection type	I : for short-circuit protection (magnetic)
Trip unit rating	100 A at 65 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

### Complementary

Instantaneous protection pick- up adjustment type li	Adjustable 9 settings
[li] instantaneous protection pick-up adjustment range	614 x ln
Earth-leakage protection	Without

#### **Environment**

Standards	UL 508 EN/IEC 60947-2
Product certifications	EAC CCC Marine
Pollution degree	3 conforming to IEC 60947-1

Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-5085 °C

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	418.0 g
Package 1 Height	6.9 cm
Package 1 width	10 cm
Package 1 Length	11.7 cm
Unit Type of Package 2	S03
Number of Units in Package 2	28
Package 2 Weight	12.042 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Package 3 Height	320 mm

### Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information

## **Contractual warranty**

144	40
Warranty	18 months