

Product datasheet

Specifications



trip unit MicroLogic 2.2 G for
ComPacT NSX 100/160/250 circuit
breakers, electronic, rating 40 A, 4
poles 4d

C1042G040

Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250 new generation
Product or component type	Control unit
Trip unit name	Micrologic 2.2 G
Trip unit technology	Electronic
Range compatibility	ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX250
Device application	Generator
Poles description	4P
Protected poles description	4t 3t 3t + N/2
Neutral position	Left
Trip unit protection functions	LSol
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	40 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

Complementary

Long-time pick-up adjustment type I _r (thermal protection)	Adjustable 9 settings
[I _r] long-time protection pick-up adjustment range	18...40 A
Long-time protection delay adjustment type t _r	Fixed
[T _r] long-time protection delay adjustment range	15 s at 1.5 x I _r 0.35 s at 7.2 x I _r 0.5 s at 6 x I _r
Thermal memory	20 minutes before and after tripping

Short-time protection pick-up adjustment type Isd	Adjustable
[Isd] Short-time protection pick-up adjustment range	1.5...9 x Ir
Short-time protection delay adjustment type tsd	Fixed
[Tsd] Short-time protection delay adjustment range	0.14 s
Instantaneous protection pick-up adjustment type li	Fixed
[li] instantaneous protection pick-up adjustment range	600 A
Earth-leakage protection	Without
Neutral protection settings	0.5 x Ir (3t + N/2) 1 x Ir (4t) No protection (3t)
Zone selective interlocking ZSI	Without
Local signalling	Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload

Environment

Standards	UL 508 EN/IEC 60947-2
Product certifications	CCC EAC Marine
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	583 g
Package 1 Height	6.6 cm
Package 1 width	9.6 cm
Package 1 Length	14.8 cm
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Weight	10.935 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes

RoHS exemption information	Yes
-----------------------------------	---------------------

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
------------------------------	---

Contractual warranty

Warranty	18 months
-----------------	-----------
