

# Product datasheet

Specifications



trip unit MicroLogic 7.2 E for  
ComPacT NSX 100/160/250 circuit  
breakers, electronic, rating 100A, 4  
poles 4d

C1047E100

## Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250 new generation
Product or component type	Control unit
Trip unit name	Micrologic 7.2 E
Trip unit technology	Electronic
Range compatibility	ComPacT new generation NSX160 ComPacT new generation NSX100 ComPacT new generation NSX250
Device application	Distribution
Poles description	4P
Protected poles description	3t + N/2 3t 4t
Trip unit protection functions	LSIR
Protection type	L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection R : for earth-leakage protection
Trip unit rating	100 A at 40 °C
[Ue] rated operational voltage	440 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

## Complementary

Long-time pick-up adjustment type I <sub>r</sub> (thermal protection)	Adjustable 9 settings
[I <sub>r</sub> ] long-time protection pick-up adjustment range	0.4...1 x I <sub>n</sub>
Long-time protection delay adjustment type t <sub>r</sub>	Adjustable
[T <sub>r</sub> ] long-time protection delay adjustment range	15...400 s at 1.5 x I <sub>r</sub> 0.35...11 s at 7.2 x I <sub>r</sub> 0.5...16 s at 6 x I <sub>r</sub>
Thermal memory	20 minutes before and after tripping

Short-time protection pick-up adjustment type Isd	Adjustable
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir
Short-time protection delay adjustment type tsd	Adjustable
[Tsd] Short-time protection delay adjustment range	0...0.4 s
Instantaneous protection pick-up adjustment type li	Adjustable
[li] instantaneous protection pick-up adjustment range	1500 A
Earth-leakage protection	Integrated
Earth-leakage protection class	Type A
[IΔn] earth-leakage protection sensitivity adjustment range	500 mA 30 mA 5 A 100 mA 300 mA 3 A 1 A
Earth-leakage protection specific mode	OFF using the IΔn rotary switch
Earth-leakage protection time delay adjustment type Δt	Adjustable
[Δt] Earth-leakage protection time delay adjustment range	0 ms 150 ms 500 ms 60 ms 1 s
Zone selective interlocking ZSI	Without
Local signalling	Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload
Display type	LCD display
Type of measurement	Energy meter
Communication of data	Maximeters/minimeters Maintenance indicators Test reports Demand current and power Time-stamped histories and event tables Earth leakage current Energy metering Protection and alarm settings Power quality Instantaneous and demand values

## Environment

Standards	IEC 60947-2 UL 508 NEMA AB1 EN 60947-2
Product certifications	CCC CB EAC
Pollution degree	3 conforming to IEC 60947-1
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	795.0 g
Package 1 Height	10 cm
Package 1 width	11 cm
Package 1 Length	15.2 cm
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Weight	8.321 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Package 3 Height	105 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information

## Contractual warranty

Warranty	18 months
----------	-----------