

# Product datasheet

Specifications



trip unit TM80G for ComPacT NSX 100/160 circuit breakers, thermal magnetic, rating 80 A, 4 poles 4d

C104MG080

EAN Code : 3606482000711

## Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250 new generation ComPacT NSX100...250 DC new generation
Product or component type	Trip unit
Trip unit name	TM-G
Trip unit technology	Thermal-magnetic
Range compatibility	ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX100 DC
Device application	Generator
Poles description	4P
Protected poles description	4D
Neutral position	Left
Trip unit protection functions	LI
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	80 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz 750 V DC
Network type	AC DC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

## Complementary

Long-time pick-up adjustment type I <sub>r</sub> (thermal protection)	Adjustable
[I <sub>r</sub> ] long-time protection pick-up adjustment range	0.7...1 x I <sub>n</sub>
Long-time protection delay adjustment type t <sub>r</sub>	Fixed
[T <sub>r</sub> ] long-time protection delay adjustment range	120...400 s at 1.5 x I <sub>n</sub>
Neutral protection settings	1 x I <sub>r</sub> (4D)

Instantaneous protection pick-up adjustment type li	Fixed
[li] instantaneous protection pick-up adjustment range	200 A
Earth-leakage protection	Without

## Environment

Standards	EN/IEC 60947-2
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60947-1
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16 cm
Package 1 Width	10 cm
Package 1 Length	16 cm
Package 1 Weight	1.2 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	32
Package 2 Height	32 cm
Package 2 Width	30 cm
Package 2 Length	41 cm
Package 2 Weight	38400 g
Unit Type of Package 3	P12
Number of Units in Package 3	384
Package 3 Height	150 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	460800 g

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	<a href="#">Yes</a>

# Contractual warranty

---

Warranty 18 months

Recommended replacement(s)