

# Product datasheet

Specifications



trip unit TM125D for ComPacT NSX 160/250 circuit breakers, thermal magnetic, rating 125 A, 3 poles 3d

C163TM125

## Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250 new generation
Product or component type	Trip unit
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Range compatibility	ComPacT new generation NSX160 ComPacT new generation NSX250
Device application	Distribution
Poles description	3P
Protected poles description	3t
Trip unit protection functions	LI
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	125 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

## Complementary

Long-time pick-up adjustment type I <sub>r</sub> (thermal protection)	Adjustable
[I <sub>r</sub> ] long-time protection pick-up adjustment range	0.7...1 x I <sub>n</sub>
Long-time protection delay adjustment type t <sub>r</sub>	Fixed
[T <sub>r</sub> ] long-time protection delay adjustment range	120...400 s at 1.5 x I <sub>n</sub> 15 s at 6 x I <sub>r</sub>
Short-time protection pick-up adjustment type I <sub>sd</sub>	Fixed
[I <sub>sd</sub> ] Short-time protection pick-up adjustment range	1250 A

Short-time protection delay adjustment type tsd	Fixed
Earth-leakage protection	Without

## Environment

Standards	UL 508 EN/IEC 60947-2
Product certifications	Marine EAC CCC
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	398.0 g
Package 1 Height	6.8 cm
Package 1 width	10 cm
Package 1 Length	11.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	28
Package 2 Weight	11.474 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information

## Contractual warranty

Warranty	18 months
----------	-----------