


# Product datasheet

Specifications



trip unit MicroLogic 4.2 AL for ComPacT NSX 160/250 circuit breakers, electronic, rating 160A, 3 poles 3d

C1634A160

## Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250 new generation
Product or component type	Control unit
Trip unit name	Micrologic 4.2 AL
Trip unit technology	Electronic
Range compatibility	ComPacT new generation NSX160 ComPacT new generation NSX250
Device application	Distribution
Poles description	3P
Protected poles description	3t
Trip unit protection functions	LSol
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	160 A at 40 °C
[Ue] rated operational voltage	440 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

## Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 9 settings
[Ir] long-time protection pick-up adjustment range	0.4...1 x In
Long-time protection delay adjustment type tr	Fixed
[Tr] long-time protection delay adjustment range	11 s at 7.2 x Ir 16 s at 6 x Ir 400 s at 1.5 x Ir
Thermal memory	20 minutes before and after tripping
Short-time protection pick-up adjustment type Isd	Adjustable

<b>[I<sub>sd</sub>] Short-time protection pick-up adjustment range</b>	1.5...10 x I <sub>r</sub>
<b>Short-time protection delay adjustment type tsd</b>	Fixed
<b>[T<sub>sd</sub>] Short-time protection delay adjustment range</b>	0.02 s
<b>Instantaneous protection pick-up adjustment type li</b>	Fixed
<b>[I<sub>i</sub>] instantaneous protection pick-up adjustment range</b>	2400 A
<b>Earth-leakage protection</b>	Integrated
<b>Earth-leakage protection class</b>	Type A
<b>[I<sub>Δn</sub>] earth-leakage protection sensitivity adjustment range</b>	500 mA 3 A 30 mA 300 mA 1 A 5 A 100 mA
<b>Earth-leakage protection specific mode</b>	OFF using the I <sub>Δn</sub> rotary switch
<b>Earth-leakage protection time delay adjustment type Δt</b>	Adjustable
<b>[Δt] Earth-leakage protection time delay adjustment range</b>	500 ms 0 ms 150 ms 60 ms 1 s
<b>Zone selective interlocking ZSI</b>	Without
<b>Local signalling</b>	Flashing LED (green) for ready to operate LED 105 % I <sub>r</sub> (red) for overload LED 90 % I <sub>r</sub> (orange) for overload Color indicator (yellow) for residual current

## Environment

<b>Standards</b>	UL 508 IEC 60947-2 NEMA AB1 EN 60947-2
<b>Product certifications</b>	EAC CB CCC
<b>Pollution degree</b>	3 conforming to IEC 60947-1
<b>IP degree of protection</b>	IP40 conforming to IEC 60529
<b>Ambient air temperature for operation</b>	-25...70 °C
<b>Ambient air temperature for storage</b>	-40...85 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	600.0 g
<b>Package 1 Height</b>	9.5 cm
<b>Package 1 width</b>	11 cm
<b>Package 1 Length</b>	15 cm
<b>Unit Type of Package 2</b>	S03

<b>Number of Units in Package 2</b>	10
<b>Package 2 Weight</b>	6.374 kg
<b>Package 2 Height</b>	30 cm
<b>Package 2 width</b>	30 cm
<b>Package 2 Length</b>	40 cm

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------