

Product datasheet

Specifications



trip unit MicroLogic 2.2 G for ComPacT NSX 160/250 circuit breakers, electronic, rating 160 A, 3 poles 3d

C1632G160

Main

| | |
|--------------------------------|--|
| Range | ComPacT new generation |
| Range of product | ComPacT NSX100...250 new generation |
| Product or component type | Control unit |
| Trip unit name | Micrologic 2.2 G |
| Trip unit technology | Electronic |
| Range compatibility | ComPacT new generation NSX160 ComPacT new generation NSX250 |
| Device application | Generator |
| Poles description | 3P |
| Protected poles description | 3t |
| Trip unit protection functions | LSol |
| Protection type | L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection |
| Trip unit rating | 160 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Circuit breaker mounting mode | Fixed |

Complementary

| | |
|---|---|
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings |
| [Ir] long-time protection pick-up adjustment range | 63...160 A |
| Long-time protection delay adjustment type tr | Fixed |
| [Tr] long-time protection delay adjustment range | 15 s at 1.5 x Ir 0.35 s at 7.2 x Ir 0.5 s at 6 x Ir |
| Thermal memory | 20 minutes before and after tripping |
| Short-time protection pick-up adjustment type Isd | Adjustable |

| | |
|--|---|
| [Isd] Short-time protection pick-up adjustment range | 1.5...9 x Ir |
| Short-time protection delay adjustment type tsd | Fixed |
| [Tsd] Short-time protection delay adjustment range | 0.14 s |
| Instantaneous protection pick-up adjustment type li | Fixed |
| [li] instantaneous protection pick-up adjustment range | 2400 A |
| Earth-leakage protection | Without |
| Zone selective interlocking ZSI | Without |
| Local signalling | Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | EN/IEC 60947-2 UL 508 |
| Product certifications | CCC Marine EAC |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -25...70 °C |
| Ambient air temperature for storage | -50...85 °C |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 430.0 g |
| Package 1 Height | 6.8 cm |
| Package 1 width | 10 cm |
| Package 1 Length | 11.5 cm |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 24 |
| Package 2 Weight | 10.776 kg |
| Package 2 Height | 30 cm |
| Package 2 width | 30 cm |
| Package 2 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |

Contractual warranty

Warranty

18 months