

Product datasheet

Specifications



trip unit MicroLogic 2.3 for ComPacT NSX 630 circuit breakers, electronic, rating 630A, 3 poles 3d

C6332D630

Main

Range	ComPacT new generation
Range of product	ComPacT NSX400...630 new generation
Product or component type	Control unit
Trip unit name	Micrologic 2.3
Trip unit technology	Electronic
Range compatibility	ComPacT new generation NSX630
Device application	Distribution
Poles description	3P
Protected poles description	3t
Trip unit protection functions	LSol
Protection type	L : for overload protection (long time) So : for short time short-circuit protection with fixed delay I : for instantaneous short-circuit protection
Trip unit rating	630 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz
Network type	AC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

Complementary

Long-time pick-up adjustment type Ir (thermal protection)	Adjustable 9 settings
[Ir] long-time protection pick-up adjustment range	250...630 A
Long-time protection delay adjustment type tr	Fixed
[Tr] long-time protection delay adjustment range	11 s at 7.2 x Ir 16 s at 6 x Ir 400 s at 1.5 x Ir
Thermal memory	20 minutes before and after tripping
Short-time protection pick-up adjustment type Isd	Adjustable 9 settings
[Isd] Short-time protection pick-up adjustment range	1.5...10 x Ir

Short-time protection delay adjustment type tsd	Fixed
[Tsd] Short-time protection delay adjustment range	0.02 s
Instantaneous protection pick-up adjustment type li	Fixed
[li] instantaneous protection pick-up adjustment range	6900 A
Earth-leakage protection	Without
Zone selective interlocking ZSI	Without
Local signalling	Flashing LED (green) for ready to operate LED 105 % Ir (red) for overload LED 90 % Ir (orange) for overload

Environment

Standards	UL 508 EN/IEC 60947-2
Product certifications	CCC Marine EAC
Pollution degree	3 conforming to IEC 60947-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.406 kg
Package 1 Height	13.5 cm
Package 1 width	17.5 cm
Package 1 Length	21.5 cm
Unit Type of Package 2	P06
Number of Units in Package 2	32
Package 2 Weight	71.708 kg
Package 2 Height	50 cm
Package 2 width	60 cm
Package 2 Length	80 cm
Unit Type of Package 3	S03
Number of Units in Package 3	4
Package 3 Weight	7.901 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration

Mercury free	Yes
---------------------	-----

RoHS exemption information	Yes
-----------------------------------	-----

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
------------------------------	---

Contractual warranty

Warranty	18 months
-----------------	-----------
