



Interface module for series connection up to 4 contact-based sensors.

## Technical details

### General data

Approval:	CE, UKCA, cULus Listed, TÜV, EAC (Eurasian)
Application range:	Fail-safe

### Technical data

#### Electrical data

Purpose of U1:	Versorgung des Moduls
Supply voltage (V):	24 - 24 V
Type of supply voltage U1:	DC
Power consumption DC:	3.5
Max. device circuit breaker:	6 A träge / 10 A flink

#### Inputs

Number of digital inputs:	8
U input to EN 61131-2 Type 1:	24 V DC

#### Semiconductor outputs

DC voltage at output:	24 V DC
Utilisation cat. to EN 60947-1:	DC-12

#### Test clock outputs

Number of test pulse outputs:	2
-------------------------------	---

#### Relay outputs

Relay contact material:	AgCdO
-------------------------	-------

Environmental data	
Climatic suitability to ...:	EN 60068-2-78
Ambient temperature:	-10 - 55 °C
EMC to standard ...:	EN 60947-5-1, EN 60947-5-3, EN 61000-6-2, EN 61000-6-4, EN 61326-3-1
Vibration to standard ...:	EN 60068-2-6
Clearance & creepage dist. to:	EN 60947-1
Overvoltage category:	III
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Protection type, mounting:	IP54
Protection type, housing:	IP40
Terminal protection type:	IP20
Mechanical data	
Mounting position:	beliebig
Housing material lower section:	PC
Housing material front plate:	PC
Housing material upper part:	PC
Connection terminal:	Federkraftklemme, Schraubklemme
Terminal style:	steckbar
Flex. cond. c/s AWG info:	24 - 12 AWG
Height dimension:	98
Width dimension:	22.5
Depth dimension:	120
Net weight:	105
Gross weight:	115
Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes

RoHS exceptions:	yes
RoHS except.s acc. to direct.:	7a, 7c I
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead, Lead oxide
%-part of the pollutant:	> 0,1%
CAS No.:	7439-92-1, 1317-36-8
WEEE klassifikation (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27242208
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000024
ETIM Reference Feature:	EC001423

## Obligatory accessories



750004

PNOZ s Setscrew terminals 22,5mm



751004

PNOZ s Setspring loaded terminals 22,5mm