HKF1-11



Products Low Voltage Prod	ucts and Systems Control Products Manual Motor Starters Manual Motor Starters Accessories
_	ledium voltage AC drives Industrial drives ACS2000
Parts & Services Drives N	ledium voltage AC drives Special purpose drives ACS1000
Parts & Services Drives N	ledium voltage AC drives Special purpose drives ACS5000
Parts & Services Drives M	ledium voltage AC drives Special purpose drives ACS6000
General Information	
Extended Product Type:	HKF1-11
Product ID:	1SAM201901R1001
EAN:	4013614320354
Catalog Description:	HKF1-11 Auxiliary Contact
Long Description:	HKF1-11 Auxcontact for frontmounting
Additional Information	
ABS Certificate: Accessory Type:	1SAA963001-0101 Auxiliary Contact
Ambient Air Temperature:	Operation -20 +55 °C
	Storage -50 +80 °C
BV Certificate:	1SAA963000-0204
CB Certificate:	1SAA963003-2001
CCC Certificate:	1SAA918002-3802
Connecting Capacity Auxiliary UL/CSA:	Circuit Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG
Connecting Capacity Auxiliary	Circuit: Flexible with Ferrule 1/2x 0.75 1.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 1.5 mm ² Flexible 1/2x 0.75 1.5 mm ² Rigid 1/2x 1.0 2.5 mm ²
Contact Rating UL/CSA:	B300 R300
Core Credit:	0.00
Country of Origin:	Bulgaria (BG)
Customs Tariff Number:	85365080
DNV Certificate:	1SAA963001-0303
Data Sheet, Technical Informa	
Declaration of Conformity - CE	 1SAD938501-0191 1SAD938516-0060 1SAD938502-0188 1SAD938504-0183 1SAD938502-0190 1SAD938510-0125
E-nummer:	3112001
EAC Certificate:	1SAA963000-2701
EAN:	4013614320354
EPLAN Catalog Tree:	Electrical engineering / Protection devices / Motor overload switch
ETIM 4:	EC002498 - Accessories for low-voltage switch technology
ETIM 5:	EC000041 - Auxiliary contact block
ETIM 6:	EC000041 - Auxiliary contact block
GL Certificate:	1SAA963001-0401 1SAA963000-0402

IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	2CDC131011M6802
	2CDC131034M6801 2CDC131022M6802
Invoice Description:	HKF1-11 Aux-contact for frontmounting
LR Certificate:	1SAA963001-0501
	1SAA963001-0502
	1SAA963000-0505
Maximum Operating Voltage UL/CSA:	Main Circuit 250 V AC
Minimum Order Quantity:	1 piece
Mounting Position:	Position 1 to 6
Number of Auxiliary Contacts NC:	1
Number of Auxiliary Contacts NO:	1
Object Classification Code:	Q
Package Level 1 EAN:	4013614481413
Package Level 1 Gross Weight:	0.195 kg
Package Level 1 Height:	50 mm
Package Level 1 Length:	36 mm
Package Level 1 Units:	10 piece
Package Level 1 Width:	148 mm
Package Level 2 EAN:	4013614522727
Package Level 2 Height:	210 mm
Package Level 2 Length:	395 mm
Package Level 2 Width:	280 mm
Part Type:	New
Part Type: Product Main Type:	New HKF1
Product Main Type:	HKF1
Product Main Type: Product Name:	HKF1 Auxiliary Contact
Product Main Type: Product Name: Product Net Depth:	HKF1 Auxiliary Contact 26.5 mm
Product Main Type: Product Name: Product Net Depth: Product Net Height:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (240 V) 6 A (380 / 400 V) 3 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0 A
Product Main Type: Product Name: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0 A (600 V) 0 A
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Inpulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Inpulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e):	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{mp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e): Rated Operational Voltage: Recommended Screw Driver:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Width: RINA Certificate: Rated Impulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e): Rated Operational Voltage: Recommended Screw Driver: RoHS Date:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V (250 V (250 V) 0.27 A (440 V) 0 A (600 V) 0 A 250 V M3 Pozidriv 2 0276
Product Main Type: Product Name: Product Net Depth: Product Net Depth: Product Net Height: Product Net Weight: Product Net Width: RINA Certificate: Rated Inpulse Withstand Voltage (U _{imp}): Rated Insulation Voltage (U _i): Rated Operational Current AC-15 (I _e): Rated Operational Current DC-13 (I _e): Rated Operational Voltage: Recommended Screw Driver: RoHS Date: RoHS Information:	HKF1 Auxiliary Contact 26.5 mm 12.5 mm 0.015 kg 45 mm 1SAA963000-0802 Auxiliary Circuit 6 kV 250 V (240 V) 4 A (24 V) 6 A (380 / 400 V) 3 A (690 V) 1 A (125 V) 0.55 A (24 V) 2 A (250 V) 0.27 A (440 V) 0 A (600 V) 0 A (250 V 250 V 138A963001-4407

Short Description:	HKF1-11 Auxcontact for frontmounting
Standards:	IEC/EN 60947-1
	IEC/EN 60947-4-1
	IEC/EN 60947-5-1
	UL 60947-1
	UL 60947-4-1
Suitable For:	MS116
	MS132
	MO132
Suitable for Product Class:	Manual Motor Starter
Tightening Torque:	Auxiliary Circuit 0.8 1.2 N·m
Tightening Torque UL/CSA:	Auxiliary Circuit 7 in Ib
UL Certificate:	UL_E137861
UNSPSC:	39121500
Wire Stripping Length:	Auxiliary Circuit 8 mm
cUL Certificate:	cUL_E137861
eClass:	7.0 27371302
/here Used (as a spare part for	r "Products")

Where Used (as a spare part for "Products")

4 Products

ldentifier	Description	Qty	Unit Of Measure
ACS 1000	No Description Available	1	piece
ACS 2000	No Description Available	1	piece
ACS 5000 Water Cooled	No Description Available	1	piece
ACS 6000	No Description Available	1	piece

Filter

Filter

Product specific part data

4	Products	

Product	Category	Drive Part Category
ACS 2000	ACS2000	Switches, Relays, Contactors
ACS 1000	ACS1000	Switches, Relays, Contactors
ACS 5000 Water Cooled	ACS5000	Switches, Relays, Contactors
ACS 6000	ACS6000	Switches, Relays, Contactors

