

TRANSPARENT HOLDERS PMF

for serieFLAT cable tags 4 mm

□

PMF holders are specifically designed to accommodate pairs of appropriately sized cables.

It is advisable to select the holder size based on the actual external diameter of the cable rather than its indicative c.s.a, due to variations in insulation thickness and conductor format.

Consult us for holders in other lengths.

Use holders only with designated cable tags of the same length.

Certificates

□ 2011/65/EU

TRANSPARENT HOLDERS PMF

Technical characteristics

Dimensional form	Transparent holder
Material	Plasticised transparent PVC
UL94 class	V0
Min operating temperature range	-40 °C
Max operating temperature range	80 °C

□□

TRANSPARENT HOLDERS PMF

List of products

PMF-00

Minimum outside diameter 1.3 mm
 Maximum outside diameter 2.2 mm
 Minimum section 0.25 mm²
 Nominal section 0.5 mm²

Type	Length	Pack qty
90000	10 mm	8,000
90010	12 mm	7,000
90020	15 mm	6,000
90040	20 mm	4,000
90070	30 mm	2,000
90090	40 mm	5,000

PMF-01

Minimum outside diameter 2 mm
 Maximum outside diameter 3.7 mm
 Minimum section 0.5 mm²
 Nominal section 2.5 mm²

Type	Length	Pack qty
90180	1000 mm	25
90100	10 mm	6,000
90110	12 mm	5,000
90120	15 mm	4,000
90140	20 mm	3,000
90170	30 mm	2,000
90190	40 mm	1,000

PMF-02

Minimum outside diameter 3.4 mm
 Maximum outside diameter 4.3 mm
 Minimum section 2.5 mm²
 Nominal section 4 mm²

Type	Length	Pack qty
90200	10 mm	4,000
90210	12 mm	4,000
90220	15 mm	3,000
90240	20 mm	2,000
90270	30 mm	1,000
90290	40 mm	1,000

PMF-04

Minimum outside diameter 6 mm
 Maximum outside diameter 10 mm
 Minimum section 10 mm²
 Nominal section 25 mm²

Type	Length	Pack qty
90400	10 mm	2,000
90410	12 mm	1,000

90420	15 mm	1,000	□
90440	20 mm	500	□
90470	30 mm	500	□
90490	40 mm	500	□

PMF-05

Minimum outside diameter 9 mm
 Maximum outside diameter 15 mm
 Minimum section 25 mm²
 Nominal section 70 mm²

- | Type | Length | Pack qty | |
|---------|--------|----------|---|
| □ 90500 | 10 mm | 550 | □ |
| 90510 | 12 mm | 550 | □ |
| 90520 | 15 mm | 250 | □ |
| 90540 | 20 mm | 250 | □ |
| 90570 | 30 mm | 150 | □ |
| 90590 | 40 mm | 100 | □ |

PMF-06

Minimum outside diameter 14 mm
 Maximum outside diameter 26 mm
 Minimum section 70 mm²
 Nominal section 240 mm²

- | Type | Length | Pack qty | |
|---------|--------|----------|---|
| □ 90600 | 10 mm | 500 | □ |
| 90610 | 12 mm | 250 | □ |
| 90620 | 15 mm | 250 | □ |
| 90640 | 20 mm | 100 | □ |
| 90670 | 30 mm | 100 | □ |
| 90690 | 40 mm | 100 | □ |