connection terminal plate, 3-pole (01199)

The picture may show a similar product.

Description

Part No.: 01199

CRITO®60Classic
connection terminal plate, 3-pole
95 - 185 mm²
for busbars 20, 25, 30 x 5, 10 and section busbars

System
60Classic

Advantages of the product
Terminals with captive clamping screws
Conductor can be overlapped
Indication of nominal cross-section and tightening torque noted on the terminals.

Product group 07
Subgroup 48

Changes in the interest of developments and technical progress are reserved.
Wöhner GmbH & Co. KG, Mönchrödener Straße 10, 96472 Rödental, Germany, Tel. +49 9563 751-0

pack size 1
EAN 4021267011994

catalog page 2020 : 3.5

ECLASS 6.1 27141146
ECLASS 7.1 27141146
ETIM 4.0 EC000001
ETIM 5.0 EC000001

Approvals

Standards
IEC 61439-1:2011
IEC 60999-1:1999
IEC 60999-2:2003

Approvals
DNV GL , EAC

EAC Type: TE-3P

CCC approval: no certification required

Technical data

Details IEC
Standards
IEC 61439-1:2011
IEC 60999-1:1999
IEC 60999-2:2003

Electrical data IEC
Rated current (IEC): 350 A
rated voltage (IEC) AC: 690 V

The insulation performance of the article depends on the installation conditions.

max. permitted voltage (IEC) AC 1000 V
max. permitted voltage (IEC) DC 1500 V

rated peak withstand current I_{pk} max.: 55.8 kA

Supplementary data IEC

The following values have been verified with tests under certain conditions. Please ask Wöhner for this conditions before designing your panel.

current capacity (IEC) max.: 460 A

Mechanical data

W x H x D: 135 x 200 x 118
weight: 132.2 kg/100
poles: 3-pole
for busbars: 20, 25, 30 x 5, 10 and section busbars

Terminal points

min. cross-section: 95 mm²
max. cross-section: 185 mm²
Suitable for aluminium cables.
When using aluminium cables, observe the maintenance instructions.

für Anwendungen nach IEC / EN :
Cu und Al 95 - 185 mm² Rundleiter mehrdrähtig und Sektorleiter mehrdrähtig
Cu auch feindrähtig, direkt geklemmt

for applications acc. to IEC / EN:
Cu or Al 95 - 185mm², round stranded or sector-shaped stranded cables
also fine stranded Cu cables (direct clamping)