

universal busbar support (01602)



The picture may show a similar product.

Description

Part No.: 01602
universal busbar support
2-pole with internal screw holes
for busbars 12, 20, 30 x 5, 10

System

60Classic

Advantages of the product

With internal screw holes
can also be used as centre support

Product group 06

Subgroup 06

pack size 1

EAN 4021267016029

catalog page 2020 : 3.1

ECLASS 6.1 27400607

ECLASS 7.1 27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011

Approvals

EAC



EAC Type: SB

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2011

Electrical data IEC

rated voltage (IEC) AC: 800 V

rated voltage (IEC) DC: 1000 V

rated isolation voltage U_j AC: 1000 V

rated isolation voltage U_j DC: 1000 V

rated surge voltage U_{imp} : 6 kV

The insulation performance of the article depends on the installation conditions.

max. permitted voltage (IEC) DC 1500 V

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 0.0 W.

(The power dissipation at full load would be 0.0 W.)

Short-circuit withstand capacity:

I_{cw} up to 39.8kA - 255ms - DC busbar support separation 250 mm (20 x 10 mm busbars)

I_{cw} up to 45.7kA - 255ms - DC busbar support separation 400mm (30 x 10mm busbars)

Mechanical data

W x H x D: 13 x 136 x 45

weight: 8.3 kg/100

poles: 2-pole

for busbars: 12, 20, 30 x 5, 10

Reference

Torque for the screws of the busbar support $M_d = 4\text{Nm}$

Accessories



01363

end cover

for busbar support 01602