

busbar 20 x 10 (01624)



The picture may show a similar product.

Description

Part No.: 01624 busbar 20 x 10 length 2.40 m, tinned

System 60Classic

Advantages of the product

Tin-plated Cu busbars considerably reduce the effort of preparing the contact points. The Cu busbars are effective protected against aggressive media.

Product group 06 Subgroup 83

pack size 1EAN 4021267016241

28.03.2023

catalog page 2020 : 3.3

ECLASS 6.127370303ECLASS 7.127370303ETIM 4.0EC001522ETIM 5.0EC001522

Approvals

Standards IEC 61439-1:2011 UL 508



type number: 20x10-L EAC Type: BB-F

UL file: E123577, UL category (for USA): NMTR http://www.ul.com UL file: E123577, UL category (for Canada): NMTR7 http://www.ul.com CSA file: 110285, CSA class: 3211-37 http://directories.csa-international.org CCC approval: no certification required

Technical data

Details IEC Standards IEC 61439-1:2011

Electrical data Please respect the insulation characteristics of the busbar support for your application.

short-circuit withstandability: see product description of the used busbar support

power dissipation of the article: The power dissipation at a typical load of 80 % results to 41.0 W. (The power dissipation at full load would be 64.0 W.)

```
current at 30 K 520 A
:
```

Details UL Standards

UL 508

for UL feeder circuits >250V

considering the permitted temperature rise at the concrete installation conditions the following capacity could be accepted by UL (file E197039 max. load acc. to UL 508: 564 A Notice the rated voltage of the used busbar support in the application.

Mechanical data

 W x H x D:
 2,400 x 20 x 10

 weight:
 428.6 kg/100

 cross-section:
 200 mm²

Edge radius 0.5

Accessories



01245

busbar cover for 12 - 30 x 10 busbar, 1 m long touch protection cover



37212 current transformer 200 A / 5 A 2.5 VA / class 1 note: when used on busbars or in 630 A adapters, article 37900 is additionally required NEW



37213

current transformer 250 A / 5 A 2.5 VA / class 1 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37214

current transformer 400 A / 5 A 2.5 VA / class 1 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37215

current transformer 500 A / 5 A 2.5 VA / class 1 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37216

current transformer 600 A / 5 A 2.5 VA / class 1 note: when used on busbars or in 630 A adapters, article 37900 is additionally required

NEW



37219

current transformer 200 A / 5 A 1.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37220

current transformer 250 A / 5 A 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37221 current transformer 400 A / 5 A

current transformer 400 A / 5 A 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37222

current transformer 500 A / 5 A 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37223

current transformer 600 A / 5 A 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37232 current transformer 200 A / 5 A, with decl. of conformity 1.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required NEW



37233 current transformer 250 A / 5 A, with decl. of conformity 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required NEW



37234

current transformer 400 A / 5 A, with decl. of conformity 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37235

current transformer 500 A / 5 A, with decl. of conformity 2.5 VA / class 0.5 note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37236

current transformer 250 A / 5 A, with decl. of conformity 1.5 VA / class 0.5s note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37237

current transformer 400 A / 5 A, with decl. of conformity 2.5 VA / class 0.5s note: when used on busbars or in 630 A adapters, article 37900 is additionally required **NEW**



37238 current transformer 500 A / 5 A, with decl. of conformity 2.5 VA / class 0.5s note: when used on busbars or in 630 A adapters, article 37900 is additionally required NEW