

neutral conductor 630 A, disconnectable (03213)



The picture may show a similar product.

Description

Part No.: 03213

neutral conductor 630 A, disconnectable

screw M12 at both sides

200 mm long

System

Mounting plate

Product group 10

Subgroup 65

pack size 3

EAN 4021267032135

catalog page 2020 : 6.12

ECLASS 6.1 27141120
ECLASS 7.1 27141120
ETIM 4.0 EC002498
ETIM 5.0 EC002498

Approvals

Standards

IEC 61439-1:2011

Approvals

EAC



EAC Type: AC-P

CCC approval: no certification required

Technical data

Details IEC

Standards

IEC 61439-1:2011

Electrical data IEC

Rated current (IEC): 630 A

rated voltage (IEC) AC: 690 V

max. permitted voltage (IEC) AC: 800 V

rated voltage (IEC) DC: 440 V

max. permitted voltage (IEC) DC: 800 V

The insulation performance of the article depends on the installation conditions.

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 9.2 W.

(The power dissipation at full load would be 14.4 W.)

Mechanical data

W x H x D: 55 x 200 x 40

weight: 58.9 kg/100

poles: 1-pole

external connection M12 / 30 - 35 Nm

internal connection M10 / 25 - 30 Nm

Terminal points

Md min.: 30.0 Nm

Md max.: 35.0 Nm

Not suitable for aluminium cables !

NHUT_SCHRAUBE_M12