

neutral conductor 400 A, disconnectable (03757)



The picture may show a similar product. Description

Part No.: 03757 neutral conductor 400 A, disconnectable screw M10 at both sides 200 mm long

System Mounting plate

Product group 10 Subgroup 65

pack size 3EAN 4021267037574

catalog page 2020 : 6.12

ECLASS 6.127141120ECLASS 7.127141120ETIM 4.0EC002498ETIM 5.0EC002498

Approvals

Standards IEC 61439-1:2011

Approvals EAC EAE

EAC Type: AC-P

CCC approval: no certification required

Technical data

Details IEC Standards IEC 61439-1:2011

Electrical data IEC

Rated current (IEC):	400 A
rated voltage (IEC) AC:	690 V
max. permitted voltage (IEC) AC:	800 V

rated voltage (IEC) DC: 440 V max. permitted voltage (IEC) DC: 800 V

The insulation performance of the article depends on the installation conditions.

power dissipation of the article:

The power dissipation at a typical load of 80 % results to 3.7 W. (The power dissipation at full load would be 5.8 W.)

Mechanical data

 W x H x D:
 55 x 200 x 40

 weight:
 58.9 kg/100

 poles:
 1-pole

Terminal points

Schraube M10, 20 Nm

Accessories