



# Cembre



CERTIFIED  
ISO 9001  
Certified Quality  
Management System



CERTIFIED  
ISO 14001  
Certified Environmental  
Management System



CERTIFIED  
OHSAS 18001  
Certified Occupational  
Health & Safety  
Management System

## “Bilinear” Cordless Hole-Punch Tool Kit



### KIT-B-FL750NDE-2

**NEW GENERATION**  
18.0V - 2.0 Ah Li-Ion

- Bilinear mechanical design
- Suitable for punching stainless steel, mild steel, fibreglass and plastic sheet materials up to 3.5mm thickness
- Extensive range of punch kits available for round, square and rectangular holes

#### OPERATION

- Head rotates through 360° and pivots through 180° allowing for ease of use in confined spaces
- 80kN developed force allowing for rapid punching times
- Punching time of only 3 seconds in 3mm mild steel with a 22.6mm hole diameter (RD22.6SS)

#### BATTERY PLATFORM

- Powered by Metabo 2Ah 18V battery
- Punching capacity of 170 operations in 3mm mild steel with a 22.6mm hole diameter (RD22.6SS)

*KIT-B-FL750NDE-2 is supplied as:*

Basic tool B-FL750NDE with battery and shoulder strap
Spare battery, mod. CB 1820L
Battery charger, mod. ASC 30-36 (UK)
Puller TD-11
Puller TD-19
spiral bit Ø 11.5 mm
Plastic carrying case, mod. VAL-P57 suitable for storing the tool and accessories

**Includes the supply of 4 x round punch kits covering the most common sizes:**

KIT for round punch:	Pg	ISO
KIT-RD20.5SS	Pg13.5	ISO-20
KIT-RD22.6SS	Pg16	-
KIT-RD25.4SS	-	ISO-25
KIT-RD32.5SS	-	ISO-32





# C e m b r e

## “Bilinear” puller-type hole punching tool



### B-FL750NDE

- Head rotates through 360° and pivots through 180° allowing for ease of use in confined spaces
- Illumination of working area via 4 x LED lights
- Bi-linear mechanical design to reduce the torque generated on the operators wrist and best distribute the stresses acting on the hand
- Bi-component plastic body provides greater rigidity and greater mechanical protection
- Electronic board to manage the working cycle for additional safety and service purpose
- LED indicators on the battery show the remaining charge at any time at the press of a button



For additional information or to request a demonstration please contact your local Cembre Ltd Sales Engineer or alternatively contact Cembre Ltd Head Office using the contact details below

#### TECHNICAL FEATURES

Max Punching Ø mm	140
Dimensions mm	
Length	474
Height	136
Width	81
Battery	18.0V 2.0Ah
Weight kg (with Battery)	4,1

#### STORAGE

Type	VAL-P57
Dimensions mm L x W x H	620 x 360 x 138
Weight kg	2,4
Supplied with the tool	✓



**C e m b r e** Ltd.  
MAKING THE RIGHT CONNECTIONS

t: +44 (0) 1675 470 440  
e. sales@cembre.co.uk  
w. www.cembre.co.uk

