B-TC320NDF

MAIN APPLICATIONS

specifically designed to cut Copper, Aluminium and Telecommunications cable having Ø max 32 mm

Tool Type	Plug Type	Supplied Battery Charger Type
B-TC320NDF	PLUG EU	ASC55-EU with EUROPEAN plug
B-TC320NDFE	PLUG UK	ASC55-UK with UK plug
B-TC320NDFA	PLUG USA CAN	ASC30-36-USA/CA (115V) with USA/CANADA plug
B-TC320NDFT	PLUG NZ AUS	ASC30-36-AUS/NZ with AUSTRALIAN/NEW ZEALAND plug

BILINEAR

SMARTOOL TECHNOLOGY

- Ø 32mm
- Li-Ion 18.0V
- 2 SPEED
- SPECIAL
- 180°
- BATTERY DISPLAY
- PROTECTED
- ONE HAND
- SAFETY
- RELEASE
- SILENT
- SMOOTH
- ERGONOMIC
- BALANCED
- LED LIGHTING
- BI-COMPONENT
- ENERGY SAVE
- DURABLE
- 200k
- -15°C +50°C
- CE
- UKCA

TECHNICAL FEATURES

Max cutting Ø mm	32
Dimensions mm	
Length	443
Height	126
Width	79
Battery	18.0V 2.0Ah
Weight kg (with Battery)	4,0

STORAGE

Type	VAL-P48
Dimensions mm L x W x H	620 x 360 x 138
Weight kg	2,4
Supplied with the tool	✔

The tool is supplied as:
- Basic tool with battery and wrist strap
- Spare battery
- Battery charger
- USB cable
- Plastic carrying case suitable for storing the tool and accessories

B-TC320NDF is a new generation of hand-held cordless tools, characterised by a "Bilinear" mechanical design.

B-TC320NDF is specifically designed to cut Copper, Aluminium and telecommunication cable having a max overall diameter of 32 mm.

The blades are manufactured from high strength special Steel, heat treated to ensure a long service life. New Li-Ion 18.0V - 2.0Ah batteries offer a higher capacity, while greater cutting speed and cutting force result from a revitalised hydraulic system with double speed action.

The battery is equipped with led indicators that indicate the remaining battery life at any time by pressing the adjacent button.

The head can rotate through 180 degrees, to enable the operator to work in the most comfortable position, and can easily be opened to allow cutting of running cables.

Quieter operation, illumination of the working area via LED lights and a minimum of vibration enhance the tool's practicality.

Two batteries and charger included.

Same charger of all our tools.

Operating temperature:
-15 to +50 ° C

CEMBRE