

IES10-SW8

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



IES10 series entry-level industrial Ethernet switches are unmanaged plug-and-play switches with tough metal housing and IP40 protection level. This series supports fast Ethernet and provides an economical and practical solution for your industrial Ethernet applications.

- Economical switch with high performance
- Compact housing
- 5 or 8 RJ45 fast Ethernet ports
- Single power input: 24/48VDC(18~72VDC), 24/48VAC(18~50VAC)
- Operating temperature range: 0°C ...+60°C

General ordering data

Version	8x RJ45 10/100BaseT(X),Din-Rail(wall) mounting products, Unmanaged IE Switch
Order No.	7760048002
Type	IES10-SW8
GTIN (EAN)	6944 169638220
Qty.	1 Stück
Delivery status	This article will no longer be available in the future.
Local product	Only available in certain countries

Erstellungs-Datum March 8, 2024 4:27:30 PM CET

Katalogstand 24.02.2024 / Technische Änderungen vorbehalten

IES10-SW8

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technische Daten

General ordering data

Local product Only available in certain countries

Dimensions and weights

Height	135 mm	Height (inches)	5.315 inch
Width	53.6 mm	Width (inches)	2.11 inch
Length	106.5 mm	Length (inches)	4.193 inch
Net weight	760 g		

Temperatures

Storage temperature	-40 °C...+85 °C	Operating temperature	0 °C...+60 °C
Humidity	5 to 95 % (non-condensing)		

Approvals

EMI		EMS	IEC 61000-4-2 Electrostatic discharge: ±8kV contact discharge, ±15kV air discharge, IEC 61000-4-3 Radiated RFI: 10V/m (80MHz~1GHz);, IEC 61000-4-4 Fast transient/burst: DC/ AC power port: ±4kV; data port: ±2kV; IEC 61000-4-5 Surge: DC/AC power port: ±2kV (line- line), ±4kV (line-earth);, IEC 61000-4-6 conducted RFI: DC/AC power port: 10V (150 kHz~80MHz)
	FCC CFR47 Part 15, CISPR22 (EN 55022) Class A		
Free fall	IEC 60068-2-32	Railway	EN 50155, EN 50121-4
EMC standards	CE, FCC	Shock resistance IEC 60068-2-27	Available
Vibration resistance IEC 60068-2-6	Available	General Industry	IEC61000-6-2
Security	UL508	Hazardous environment	UL1604 Class 1 Div 2 (pending)

Cable

Twisted Pair 100 m (standard CAT5,
CAT5e LAN cable)

Power Supply

Connection type	3 pole 5.08mm pitch terminal block	Input voltage	24V DC/AC (18~72 VDC / 18~50 VAC)
Overload protection	Yes	Power consumption	≤2.9 W
Redundant power supply	No	Reverse polarity protection	Yes

Technology

Diagnosis	LED (power supply and port)	Network structure	star, line
-----------	--------------------------------	-------------------	------------

Erstellungs-Datum March 8, 2024 4:27:30 PM CET

Katalogstand 24.02.2024 / Technische Änderungen vorbehalten

IES10-SW8

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technische Daten

Environmental conditions

Humidity 5 to 95 % (non-condensing)

Guarantee

Time interval 5 years

Interfaces

LED indicator	Power LED: PWR, Port LED: Link/ACT, Speed (RJ45 port)	Number of ports	8x RJ45 10/100BaseT(X)
---------------	---	-----------------	------------------------

Technical data

Housing main material	fanless, metal	Number of ports	8x RJ45 10/100BaseT(X)
Protection degree	IP40	Type of mounting	Rail, TS 35, Wall mounting

Classifications

ETIM 6.0	EC000734	ETIM 7.0	EC000734
ETIM 8.0	EC000734	ETIM 9.0	EC000734
ECLASS 9.0	19-17-01-06	ECLASS 9.1	19-17-01-06
ECLASS 10.0	19-17-04-01	ECLASS 11.0	19-17-04-01
ECLASS 12.0	19-17-04-01	ECLASS 13.0	19-17-04-01

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	9229992a-00b9-4096-8962-200a7f33e289

Approvals

Approvals



UL File Number Search	UL Website
Certificate no. (cULusEX)	E223527

Downloads

Catalogues [Catalogues in PDF-format](#)