

## IES10-SW5

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



IES10 series entry-level industrial Ethernet switches are unmanaged plug-and-play switches with tough metal housing and IP40 protection level. This series supports fast Ethernet and provides an economical and practical solution for your industrial Ethernet applications.

- Economical switch with high performance
- Compact housing
- 5 or 8 RJ45 fast Ethernet ports
- Single power input: 24/48VDC(18~72VDC), 24/48VAC(18~50VAC)
- Operating temperature range: 0°C ...+60°C

### General ordering data

Version	5 * RJ45 10/100BaseT(X),Din-Rail(wall) mounting products, Unmanaged IE Switch
Order No.	<a href="#">7760048001</a>
Type	IES10-SW5
GTIN (EAN)	6944 169638213
Qty.	1 Stück
Delivery status	<b>Discontinued</b>
Local product	Only available in certain countries

Erstellungs-Datum March 8, 2024 4:16:43 PM CET

## IES10-SW5

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technische Daten

### General ordering data

Local product Only available in certain countries

### Dimensions and weights

Height	115 mm	Height (inches)	4.528 inch
Width	30 mm	Width (inches)	1.181 inch
Length	91.5 mm	Length (inches)	3.602 inch
Net weight	460 g		

### Temperatures

Storage temperature	-40 °C...+85 °C	Operating temperature	0 °C...+60 °C
Humidity	5 to 95 % (non-condensing)		

### Approvals

EMI		EMS	IEC 61000-4-2 Electrostatic discharge: ±8kV contact discharge, ±15kV air discharge; IEC 61000-4-3 Radiated RFI: 10V/m (80MHz~1GHz); IEC 61000-4-4 Fast transient/burst: DC/AC power port: ±4kV; data port: ±2kV; IEC 61000-4-5 Surge: DC/AC power port: ±2kV (line-line), ±4kV (line-earth); IEC 61000-4-6 conducted RFI: DC/AC power port: 10V (150 kHz~80MHz)
	FCC CFR47 Part 15, CISPR22 (EN 55022) Class A		
Free fall	IEC 60068-2-32	Railway	EN 50155, EN 50121-4
EMC standards	CE, FCC	Shock resistance IEC 60068-2-27	Available
Vibration resistance IEC 60068-2-6	Available	General Industry	IEC61000-6-2
Security	UL508	Hazardous environment	UL1604 Class 1 Div 2 (pending)

### Cable

Twisted Pair 100 m (standard CAT5, CAT5e LAN cable)

### Power Supply

Connection type	3 pole 5.08mm pitch terminal block	Input voltage	24V DC/AC (18~72 VDC / 18~50 VAC)
Overload protection	Yes	Power consumption	≤1.9 W
Redundant power supply	No	Reverse polarity protection	Yes

### Technology

Diagnosis	LED (power supply and port)	Network structure	star, line
-----------	-----------------------------	-------------------	------------

Erstellungs-Datum March 8, 2024 4:16:43 PM CET

Katalogstand 24.02.2024 / Technische Änderungen vorbehalten

## IES10-SW5

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technische Daten

### Environmental conditions

Humidity 5 to 95 % (non-condensing)

### Guarantee

Time interval 5 years

### Interfaces

LED indicator	Power LED: PWR, Port LED: Link/ACT, Speed (RJ45 port)	Number of ports	5 * RJ45 10/100BaseT(X)
---------------	---	-----------------	-------------------------

### Technical data

Housing main material	fanless, metal	Number of ports	5 * RJ45 10/100BaseT(X)
Protection degree	IP40	Type of mounting	Rail, TS 35, Wall mounting

### Classifications

ETIM 6.0	EC000734	ETIM 7.0	EC000734
ETIM 8.0	EC000734	ETIM 9.0	EC000734
ECLASS 9.0	19-17-01-06	ECLASS 9.1	19-17-01-06
ECLASS 10.0	19-17-04-01	ECLASS 11.0	19-17-04-01
ECLASS 12.0	19-17-04-01	ECLASS 13.0	19-17-04-01

### Approvals

Approvals



UL File Number Search	UL Website
Certificate no. (cULusEX)	E223527

### Downloads

Catalogues [Catalogues in PDF-format](#)