

Product datasheet

Specifications



Molded case circuit breaker, PowerPacT 4, 3P, Icu 36kA, TMD thermal magnetic trip unit, 32A rating

PP40323X

EAN Code: 5018934030104

Main

Range Of Product	PowerPacT 4
Product Or Component Type	Circuit breaker
Device Application	Distribution
Poles Description	3P
[In] Rated Current	32 A at 40 °C
[Ue] Rated Operational Voltage	415 V AC 50/60 Hz
Suitability For Isolation	Yes conforming to BS EN 60947-2
Utilisation Category	Category A
[Icu] Rated Ultimate Short-Circuit Breaking Capacity	36 kA Icu at 415 V AC 50/60 Hz
Performance Level	F
Trip Unit Name	TM-D
Trip Unit Technology	Thermal-magnetic
Trip Unit Protection Functions	LI
Control Type	Toggle
Circuit Breaker Mounting Mode	Panel-mounted

Complementary

[Ui] Rated Insulation Voltage	800 V
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ics] Rated Service Short-Circuit Breaking Capacity	36 kA at 415 V AC 50/60 Hz
Mechanical Durability	50000 cycles
Electrical Durability	50000 cycles at 440 V In/2 30000 cycles at 440 V In
Power Dissipation Per Pole	4.03 W
Mounting Support	Backplate
Mounting Position	Horizontal and vertical
Number Of Modules	3 module(s)35 mm
Protection Type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip Unit Rating	32 A at 40 °C
Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Fixed

[Ir] Long-Time Protection Pick-Up Adjustment Range	0.7...1 x In
Long-Time Protection Delay Adjustment Type Tr	Fixed
Instantaneous Protection Pick-Up Adjustment Type li	Fixed
[Ii] Instantaneous Protection Pick-Up Adjustment Range	400 A
Earth-Leakage Protection	Without
Contact Position Indicator	Yes
Width	105 mm
Depth	86 mm
Height	161 mm
Net Weight	2.05 kg
Product Destination	250 A panelboard 400/630 A panelboard
Colour	Grey

Environment

Standards	BS EN 60947-2
Electrical Shock Protection Class	Class II
Pollution Degree	3 conforming to EN/IEC 60664-1
Ip Degree Of Protection	IP40 conforming to EN/IEC 60529
Ik Degree Of Protection	IK07 conforming to EN/IEC 62262
Ambient Air Temperature For Operation	-25...70 °C
Ambient Air Temperature For Storage	-50...85 °C
Operating Altitude	0...2000 m without derating 2000...5000 m with derating

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.000 cm
Package 1 Width	25.500 cm
Package 1 Length	25.500 cm
Package 1 Weight	3.347 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	84
Package 2 Height	100.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	340.880 kg

Contractual warranty

Warranty	18 months
-----------------	-----------