

Acti9 overvoltage protection auxiliary iACTp 220...240 V AC

Local distributor code: 396735128

96735128 A9C15920

EAN Code: 3606480097904

Main

| Range | Acti9 | |
|------------------------------|---|--|
| Product Or Component Type | Overvoltage protection auxiliary (2 circuits) | |
| Device Short Name | iACTp | |
| [Uc] Control Circuit Voltage | 220240 V AC 50/60 Hz | |

Complementary

| Hold-In Power Consumption In Va | 3 VA | |
|--|--|--|
| Mounting Mode | Fixed, on the left of CT | |
| Mounting Support | DIN rail | |
| 9 Mm Pitches | 2 | |
| Height | 81 mm | |
| Width | 18 mm | |
| Depth | 60 mm | |
| Colour | White | |
| Overvoltage Category | III | |
| [Uimp] Rated Impulse Withstand Voltage | 4 kV | |
| [Ui] Rated Insulation Voltage | 440 V | |
| Standards | IEC/EN 61095 | |
| Connections - Terminals | Control circuit: tunnel type terminals 2 cable(s) 2.5 mm² flexible Control circuit: tunnel type terminals 2 cable(s) 1.5 mm² rigid Control circuit: tunnel type terminals 1 cable(s) 1.52.5 mm² rigid Control circuit: tunnel type terminals 1 cable(s) 1.52.5 mm² flexible with ferrule Control circuit: yellow clips | |
| Wire Stripping Length | 9 mm | |
| Tightening Torque | 0.8 N.m | |
| Range Compatibility | Acti9 Acti9 iCT | |
| Market Segment | Small commercial Residential | |
| Compatibility Code | IACTp | |

Environment

| Ip Degree Of Protection | IP20 conforming to IEC 60529 | |
|---------------------------------------|------------------------------|--|
| Ambient Air Temperature For Operation | -550 °C | |
| Ambient Air Temperature For | 4070 °C | |

Packing Units

| • | |
|------------------------------|----------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 1.8 cm |
| Package 1 Width | 6.7 cm |
| Package 1 Length | 8.5 cm |
| Package 1 Weight | 64 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 7.5 cm |
| Package 2 Width | 9.5 cm |
| Package 2 Length | 23 cm |
| Package 2 Weight | 770 g |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 108 |
| Package 3 Height | 30 cm |
| Package 3 Width | 30 cm |
| Package 3 Length | 40 cm |
| Package 3 Weight | 7.417 kg |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Reach Free Of Svhc | |
|---|---|
| Toxic Heavy Metal Free | |
| Mercury Free | |
| Rohs Exemption Information | Yes |
| Halogen Free Plastic Parts & Cables Product | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |