Product datasheet

Specification





voltage transformer - 230..400 V - 1 x 24 V - 160 VA

Local distributor code: 391228494

ABL6TS16B

! Discontinued on: 30 May 2024

! To be end-of-service on: 30 May 2025

(!) To be discontinued

EAN Code: 3389110585841

Main

Range Of Product	Modicon Transformer Optimized		
Product Or Component Type	Safety and isolation transformer		
Rated Power In Va	160 VA		
Input Voltage	230 V AC single phase, terminal(s): N-L1 400 V AC phase to phase, terminal(s): L1-L2		
Output Voltage	24 V AC		
Secondary Winding	Single		
Protective Cover	Without		
Ambient Air Temperature For Operation	-2050 °C		

Complementary

Input Voltage Limits	360440 V
input voitage Limits	
	207253 V
Network Frequency Limits	4763 Hz
Input Voltage Tolerance	+/- 15 V
Efficiency	88 %
Power Dissipation In W	21.8 W
Output Sustained Overvoltage	7 % (no load, hot state)
Maximum Voltage Drop At Rated Load	0.3 %
No Load Losses	9.1 W
Short-Circuit Voltage	0,0681
Output Protection Type	Against overload, protection technology: with additional protection fuses or circuit-
	breakers in Selection of Protection
	Against overvoltage, protection technology: with additional protection fuses or circuit- breakers in Selection of Protection
	Against short-circuits, protection technology: with additional protection fuses or
	circuit-breakers in Selection of Protection
Connections - Terminals	For input connection: screw type terminals, connection capacity: 5 x 4 mm² AWG 11
	For input ground connection: screw type terminals, connection capacity: 1 x 4 mm ²
	AWG 11
	For output connection: screw type terminals, connection capacity: 2 x 4 mm² AWG 11
Marking	CE
Fixing Mode	By 4 screws diameter: 5.8 mm on vertical panel, operating position: horizontal
	By 4 screws diameter: 5.8 mm on vertical panel, operating position: vertical
	By 4 screws diameter: 5.8 mm on horizontal panel with derating to 90 $\%$
Operating Altitude	3000 m

Electrical Insulation Class	Class B
Width	105.0 mm
Height	81.0 mm
Depth	112.0 mm
Net Weight	2.84 kg

Environment

Product Certifications	EAC UR DNV-GL	
Standards	UL 506	
Ip Degree Of Protection	IP20	
Environmental Characteristic	EMC conforming to EN 62041 Safety conforming to EN 61558-1 Safety conforming to EN 61558-2-6	
Protective Treatment	TC	
Ambient Air Temperature For Storage	-4080 °C	
Overvoltage Category	Class I conforming to VDE 0106-1	
Dielectric Strength	2000 V between winding and ground 4000 V between primary and secondary	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	22.500 cm
Package 1 Width	22.000 cm
Package 1 Length	20.000 cm
Package 1 Weight	3.114 kg
Unit Type Of Package 2	P06
Number Of Units In Package 2	30
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	105.940 kg

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
②	Pvc Free	


Certifications & Standards

Reach Regulation	REACh Declaration			
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)			
China Rohs Regulation	China RoHS declaration			
Environmental Disclosure	Product Environmental Profile			
Circularity Profile	No need of specific recycling operations Circularity Profile			

ABL6TS16B

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	С	G	J	Ø
105	112	81	80.5	63	5.8

Dimensions in in.


2					
а	b	С	G	J	Ø
4.13	4.41	3.19	3.17	2.48	0.23

Product datasheet


ABL6TS16B


Connections and Schema

Internal Scheme



Primary Voltage Wiring





Secondary Voltage Wiring

