


Data Sheet | Item Number: 770-505/021-000

Strain relief housing; 5-pole; for 1 cable; 11.5 ... 16.5 mm; 71 mm; black

<https://www.wago.com/770-505/021-000>



Color: ■ black



Dimensions in mm

Strain relief housing *WINSTA*® MIDI 5-pole

Choose reliable accuracy for the electrical installation at your construction site: The strain relief housing from the *WINSTA*® MIDI product line. With WAGO, you can enjoy the advantages of a large selection of expansions for the *WINSTA*® product line. *WINSTA*® MIDI with Push-in CAGE CLAMP® spring pressure connection technology is found in a broad range of individual products you can use for quick, easy, secure, tailored electrical installation. The strip length is 71 mm.

Lower costs through fast commissioning and elimination of service expenses – solutions from *WINSTA*® MIDI

The *WINSTA*® Pluggable Connection System is perfectly tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and therefore faster, more reliable, and error-free. Use of this pre-assembled system reduces time spent on assembly and installation errors at the construction site. Choose durability and quality – with protection against mismating from WAGO makes the installation of electrical components significantly easier.

- simple circuits
- rapid, structured electrical installation

Connection data

Connection 1

Pole number	5
Connectable sheathed cable diameter	11.5 ... 16.5 mm
Strip length (outer insulation)	71 mm

Physical data

Pin spacing	10 mm / 0.394 inches
Width	54.75 mm / 2.156 inches
Height	21 mm / 0.827 inches
Depth	72.7 mm / 2.862 inches

Material data

Note (material data)	Information on material specifications can be found here
Color	black
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.529 MJ
Weight	19 g

Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-92
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	25 pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454026219
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
cURus Underwriters Laboratories Inc.	UL 1977	E45171
VDE VDE Prüf- und Zertifizie- rungsinstitut	EN 61535	40029808

Downloads

Environmental Product Compliance



Compliance Search

Environmental Product
Compliance
770-505/021-000



Documentation

Bid Text

770-505/021-000	19.02.2019	xml 2.84 KB	
770-505/021-000	10.12.2014	doc 24.00 KB	

CAD/CAE-Data

CAD data

2D/3D Models
770-505/021-000



CAE data

EPLAN Data Portal
770-505/021-000



WSCAD Universe
770-505/021-000



ZUKEN Portal
770-505/021-000



1 Compatible Products

1.1 Optional Accessories

1.1.1 Marking

1.1.1.1 Marking strip



Item No.: 210-333

Marking strips; as a DIN A4 sheet; Strip
width 6 mm; Strip length 182 mm; plain;
Self-adhesive; white