



Color: Dlack

Cover WINSTA® MIDI 3-pole

The cover from the *WINSTA®* MIDI product line is the advanced solution for reliable installation. An extensive range of accessories complements the WINSTA® product line from WAGO. Our *WINSTA®* MIDI product line allows total flexibility for the installation of applications. With its Push-in CAGE CLAMP® spring pressure connection technology, it guarantees error-free, time-saving installation and offers flexibility for meeting all installation requirements.

WINSTA® MIDI solutions for your electrical installation – protected against mismating and maintenance-free

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This saves time, lowers costs, and reduces the need for servicing. Choose durability and quality – with protection against mismating from WAGO makes the electrical installation of electrical components noticeably easier.

· pre-assembled versions

• convenient installation and commissioning

Flammability class per UL94 V0	Connection data		
Mechanical data Mounting type Snap-in flange Suitable for cutout Meterial data Information on material specifications can be found here Note (material data) Information on material specifications can be found here Suitable black Finamability class per UL94 V0 Fie load 0.065 MJ	Connection 1		
Mounting typeSnap-in flangeSuitablefor cutoutMaterial dataNote (material data)Information on material specifications can be found hereeColorblackInsulation materialPolyamide (PA66)Isnability class per UL94V0Fie load0.665 MJ	Pole number	3	
Mounting typeSnap-in flangeSuitablefor cutoutMaterial dataNote (material data)Information on material specifications can be found hereeColorblackInsulation materialPolyamide (PA66)Isnability class per UL94V0Fie load0.665 MJ			
Suitablefor cutotutMaterial dataInformation on material specifications can be found hereNote (material data)Information on material specifications can be found hereColorblackInsulation materialPolyamide (PA66)Isumability class per UL94V0Fire load0.065 MJ	Mechanical data		
Material data Information on material specifications can be found here Note (material data) Information on material specifications can be found here Color black Insulation material Polyamide (PA66) Fiendad V0 Fiendad 0.065 MJ	Mounting type		Snap-in flange
Note (material data)Information on material specifications can be found hereColorblackInsulation materialPolyamide (PA66)Flammability class per UL94V0Fire load0.065 MJ	Suitable		for cutout
Note (material data)Information on material specifications can be found hereColorblackInsulation materialPolyamide (PA66)Flammability class per UL94V0Fire load0.065 MJ			
Information on material specifications can be found here Color black Insulation material Polyamide (PA66) Flammability class per UL94 V0 Fire load 0.065 MJ	Material data		
Color black Insulation material Polyamide (PA66) Flammability class per UL94 V0 Fire load 0.065 MJ	Note (material data)		
Insulation materialPolyamide (PA66)Flammability class per UL94V0Fire load0.065 MJ			Information on material specifications can be found here
Flammability class per UL94 V0 Fire load 0.065 MJ	Color		black
Fire load 0.065 MJ	Insulation material		Polyamide (PA66)
	Flammability class per UL94		V0
Weight 1.8 g	Fire load		0.065 MJ
	Weight		1.8 g

Data Sheet | Item Number: 770-643

https://www.wago.com/770-643



Environmental requirements	
Processing temperature	-5+40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data	
Product Group	20 (Winsta)
eCl@ss 10.0	27-44-06-92
eCl@ss 9.0	27-44-06-03
ETIM 8.0	EC002863
ETIM 7.0	EC002863
PU (SPU)	100 pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332755443
Customs tariff number	39269097900

Environmental Product Compliance

RoHS Compliance Status

Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 770-643	$\underline{\downarrow}$

Documentation

Bid Text			
770-643	19.02.2019	xml 2.68 KB	\downarrow
770-643	13.01.2015	doc 23.00 KB	\downarrow

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 770-643	WSCAD Universe 770-643
	ZUKEN Portal 770-643

Subject to changes. Please also observe the further product documentation!