

ARCA 405021S



Sample image

Order symbol : ARCA 405021S

Product nr : 8120105

UL Code : UL508A

Description : Cabinet, PC


Remarks : Grey cover, Swinghandle, hinges on the short side

EAN : 6418074079886

El. number :

- Finland : 3423184
- Denmark : 8212091757

Including : Cabinet base. door with PUR gasket. mounting plate. screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.



Dimensions :	Height	Width	Depth
mm :	400	500	210
inch :	19.69	15.75	8.58

Materials :

Material : Polycarbonate

Accessories :

MPX ARCA 5040	Mounting plate (450x350 mm) (450 x 350 x 5)
MPMP ARCA 5040	Mounting plate multiperforated (450x350x2 mm - ø3.6 mm)
DSP ARCA HRS	Door stopper ARCA, horizontal, right, small
DRS ARCA 405021	DIN rail frame set (485 x 385 x 35)

Base colour :	RAL_7035
Cover colour :	RAL 7035 -light grey
Gasket material :	Polyurethane

DSP ARCA HLS	Door stopper ARCA, horizontal, left, small
MPP ARCA 4050	Mounting plate perforated (450x350x2 mm - 26x11 mm)
MPS ARCA 5040	Mounting plate (450x350x2 mm) (450 x 350 x 2)
PMK ARCA 50	PoleMounting kit, for pole ø100-300mm (485 x 385 x 35)
IDS ARCA 4050	Inner door set
RCS ARCA 4050	Rain canopy set for size 4050 (30 x 500 x 20)

Temperatures :

Temperature °C (short term) :	-40 ... 120
Temperature °C (continuous) :	-40 ... 80
Temperature °F (short term) :	-40 ... 250
Temperature °F (continuous) :	-40 ... 175

Ratings :

Ingress protection (EN 60529):	IP66;
Impact Resistance (EN 62262):	IK10;
electrical_insulation :	Totally insulated
Halogen free (DIN/VDE 0472, Part 815) :	Yes
UV resistance :	UL 746C
Flammability Rating :	UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C :	960C

Certificates :

Certificate FI 40467