Specifications



Isobar A - neutral bar - 1N - for distribution board - 18 ways SP+N

Local distributor code: 396793814

SEA9NA18

EAN Code: 5018934963334

Main

Range of product	Acti9
Product or component type	Neutral bar
enclosure mounting	Wall mounted
Door type	Overall
Enclosure material	Steel
Surface treatment	Ероху
Surface finish	Powder paint
poles description	1P + N

Complementary

[le] rated operational current	125 A at 230/240 V AC 125 A at 110 V AC
breaking capacity	25 kA
Protection device name	IC60H
Product destination	Distribution board
Number of ways	18 ways outgoer
Provided equipment	Neutral bar Busbar link 4 Cover
IP degree of protection	IP2X internal conforming to BS EN 60529
IK degree of protection	IK05 conforming to BS EN 60529
Colour	White (RAL 9001)

Environment

Standards	BS EN 60439-3
Ambient air temperature for operation	-3570 °C
Ambient air temperature for storage	-4080 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.100 cm
Package 1 Width	8.000 cm

 Package 1 Length
 70.000 cm

 Package 1 Weight
 300.000 g

Contractual warranty

Warranty

18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information