

Product datasheet

Specifications



Acti9 Isobar A - din rail enclosure - 12 ways - steel

Local distributor code:
396793720

SEA9DE24

EAN Code: 5018934963280

Main

Range	Acti9
Product name	Acti9 Isobar A
Product or component type	Loose enclosure
Device application	Distribution
enclosure mounting	Surface
Door type	Left opening hinged plain door with plastic latch
Provided equipment	Earth terminal block Enclosure DIN rail Cover Door Back plate

Complementary

Number of ways	12 ways (1P)
Number of horizontal rows	1
Enclosure material	Folded sheet steel: RAL 9001 epoxy powder coat
Cable entry	Knock-out 25 mm (top and bottom) Knock-out 25 mm (rear) Knock-out 25 mm (side)
Height	300 mm
Width	345 mm
Depth	117 mm

Environment

IP degree of protection	IP3x
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	31.0 cm
Package 1 Length	35.0 cm
Package 1 Weight	4.087 kg
Unit Type of Package 2	P12

Number of Units in Package 2	54
Package 2 Height	104.0 cm
Package 2 Width	100.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	235.86 kg

Contractual warranty

Warranty	18 months
-----------------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information
