

# Product datasheet

Specifications



## Acti9 IsoBar B - switch disconnecter - 200A - 4P

Local distributor code:  
405638637

SEA9PNI2004

EAN Code: 5018934008448

### Main

Range	Acti9
Product or component type	Switch disconnecter
Device application	Distribution

### Complementary

[Ie] rated operational current	200 A at 415 V AC
poles description	4P
Connections - terminals	Pad terminal of copper material for M6 connection
Tightening torque	15 N.m
Product destination	Distribution board
Utilisation category	AC-22

### Environment

Standards	BS EN 60947-3
-----------	---------------

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.000 cm
Package 1 Width	48.000 cm
Package 1 Length	51.000 cm
Package 1 Weight	11.442 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	16
Package 2 Height	95.000 cm
Package 2 Width	100.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	203.072 kg

### Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Rohs Exemption Information Yes

Halogen Free Plastic Parts Product

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile No need of specific recycling operations